

1387

Blaq

**CONSTRUCTION & DESIGN**

- Surface mounted LED exterior wall light
- Constructed in pressure die cast aluminium alloy and finished in durable dark grey powdercoat paint
- Unique luminaire designed for both general illumination and for highlighting architectural features
- One way light distribution for direct and indirect illumination with low glare
- Clear tempered glass and silicone seals provides IP54 protection

TECHNICAL PERFORMANCE


- 6W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Available in 3K colour temperature with low colour shift over time

OPTICAL & THERMAL PERFORMANCE

- Reflector and customised heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied completely assembled with integral non-dimmable driver and terminal block
- Input voltage 220-240V, 50/60 Hz



	ONE WAY	Weight (kg) 1.0	3K CRI >85					CE	IP54
--	---------	--------------------	---------------	--	--	--	--	----	------

TOTAL SYSTEM POWER CONSUMPTION = 6 W**CODE ORDERING GUIDE:** PRODUCT CODE – COLOUR SUFFIX

Example: 1387-3K-12

WATTAGE	COLOUR TEMPERATURE	> 55° WIDE	HOT LED LUMENS
		PRODUCT CODES	
6W	3K	1387-3K	520

Supplied as standard integral non-dimmable driver

COLOUR OPTION: add suffix after the code

-12 Dark grey -03 White Special order