

1004

Mylo



70

**CONSTRUCTION & DESIGN**

- Low profile recessed LED adjustable downlight
- Constructed in die cast aluminium alloy and finished in satin white and matte black powdercoat paint
- Low profile adjustable LED downlight with up to 22W system power and high lumen output
- Designed with distinctive lines creating a simple and contemporary downlight
- Clear tempered glass providing IP44 protection
- Ideal for spaces such as foyers, hotels, corridors, retail spaces, function rooms, living areas and bedrooms

**TECHNICAL PERFORMANCE**


- 8W, 13W or 22W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K, and 5K colour temperature with low colour shift over time

**OPTICAL & THERMAL PERFORMANCE**

- Reflector and customised heatsink provides premium optical and thermal performance
- Thermodynamically efficient heatsink design
- Efficient optical control in various beam angles with no harsh cut off and ultra low glare

**ELECTRICAL SYSTEM**

- Supplied complete with remote leading and trailing edge mains dimmable driver, which is compatible with a range dimming systems
- All drivers come with quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz



Weight (kg)	3K and 4K	5K							IP44
0.3	CRI >85	CRI >75	95	30°	F	SELV			

**TOTAL SYSTEM POWER CONSUMPTION = 8W / 13W / 22W**

**CODE ORDERING GUIDE:** PRODUCT CODE /DIMMING SUFFIX (if required) – COLOUR SUFFIX  
 Example: 1004-SP-3K-8W-01 or 1004-SP-3K-8W/DALI-01

WATT	COLOUR TEMP.	24° SP	36° FL	47° WFL	55° VWFL	HOT LED LUMENS
		PRODUCT CODES				
8W	3K	1004-SP-3K-8W	1004-FL-3K-8W	1004-WFL-3K-8W	-	828
	4K	1004-SP-4K-8W	1004-FL-4K-8W	1004-WFL-4K-8W	-	870
	5K	1004-SP-5K-8W	1004-FL-5K-8W	1004-WFL-5K-8W	-	888
13W	3K	1004-SP-3K-13W	1004-FL-3K-13W	-	1004-VWFL-3K-13W	1519
	4K	1004-SP-4K-13W	1004-FL-4K-13W	-	1004-VWFL-4K-13W	1607
	5K	1004-SP-5K-13W	1004-FL-5K-13W	-	1004-VWFL-5K-13W	1646
22W	3K	1004-SP-3K-22W	1004-FL-3K-22W	-	1004-VWFL-3K-22W	2414
	4K	1004-SP-4K-22W	1004-FL-4K-22W	-	1004-VWFL-4K-22W	2584
	5K	1004-SP-5K-22W	1004-FL-5K-22W	-	1004-VWFL-5K-22W	2618

DIMMING OPTIONS: ADD SUFFIX AFTER THE CODE		8W	13W	22W
/DALI	Dali Dimming	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
	Switch Dim	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓	✓
Leading & Trailing edge mains dimming		STANDARD	STANDARD	STANDARD

**TRIM COLOUR OPTIONS: ADD SUFFIX AFTER THE CODE**

- 01 Satin White
- 06 Matte Black