

LEGEND

	ELECTRICAL SERVICES SWITCHBOARD.
	SWITCHBOARD / CONTROL PANEL NOT PROVIDED AS PART OF THE ELECTRICAL SUBCONTRACT.
	SINGLE POWER OUTLET.
	DOUBLE POWER OUTLET.
	DOUBLE POWER OUTLET C/W USB CHARGER.
	SPECIAL PURPOSE POWER OUTLET.
	SINGLE PHASE ISOLATOR.
	THREE PHASE ISOLATOR.
	ELECTRICAL JUNCTION BOX / RISER AS NOTED.
	ELECTRICAL CABLE TRAY / LADDER AS NOTED.
	CONDUIT ROUTE.
	x DENOTES CONDUIT TYPE.
	ELECTRICAL PIT, TYPE AS NOTED.
	HAND DRYER CONNECTION.
	LIGHTING PRESENCE DETECTOR SWITCH.
	LIGHTING CONTROL SWITCH PANEL, TYPE AS NOTED.
	ONE-WAY LIGHT SWITCH.
	TWO-WAY LIGHT SWITCH.
	CIRCUIT LINE.
	SWITCH LINE.
	POWER CIRCUIT DESIGNATION. DENOTES DB AND CIRCUIT.
	LIGHTING CONTROL CHANNEL REFERENCE.
	ELECTRICAL EQUIPMENT AS NOTED.
	RJ45 COMMUNICATIONS OUTLET ALL TO CR-A, UNLESS NOTED AS "T" THEN TO CR-T.
	RJ45 GAMING LINK OUTLET.
	FIRE INDICATOR PANEL.
	NBN PREMISES CONNECTION DEVICE.
	NBN NETWORK TERMINATION DEVICE.
	FLOOR BOX, TYPE AS NOTED.
	GAMING FIBRE.
	HDMI OUTLET, TYPE AS NOTED.
	M1 SUPPLY AUTHORITY CODE COMPLIANT LV MAXIMUM DEMAND TARIFF METER.
	M2 PRIVATE MULTIFUNCTION METER.
	FUSE.
	SINGLE PHASE.
	THREE PHASE.
	CURRENT TRANSFORMER C/W REMOVABLE LINK.
	FUSE LINK.
	COMBINED FUSE SWITCH.

LEGEND

	CIRCUIT BREAKER.
	ISOLATOR.
	RESIDUAL CURRENT DEVICE.
	CONTACTOR – NORMALLY OPEN.
	CONTACTOR – NORMALLY CLOSED.
	REFER TO DETAIL NOTED FOR THE AREA SHOWN HATCHED. ADDITIONAL OUTLETS & FITTINGS MAY BE SHOWN ON DETAIL.
	E1: WHITE RECESSED GENERAL LED EMERGENCY LIGHT.
	E2: WHITE SURFACE MOUNTED GENERAL LED EMERGENCY LIGHT.
	E3 EX: WHITE EMERGENCY LED EXIT LIGHT, BACK OF HOUSE.
	E4 EX: WHITE EMERGENCY LED EXIT LIGHT, FRONT OF HOUSE.
	E5 EX: WHITE EMERGENCY LED EXIT LIGHT, SURFACE MOUNTED, FRONT OF HOUSE.
	E6: BLACK RECESSED GENERAL LED EMERGENCY LIGHT.
	E7 EX: BLACK EMERGENCY LED EXIT LIGHT, FRONT OF HOUSE.
	Lx: LIGHT FITTING C/W NON-MAINTAINED EMERGENCY BATTERY PACK. TYPE AS NOTED.
	NO LONGER REQUIRED.
	NO LONGER REQUIRED.
	L3: WHITE RECESSED 300 x 600 FLAT PANEL TROFFER.
	L4: WHITE RECESSED 300 x 1200 FLAT PANEL TROFFER.
	L5: 1200 BATTEN C/W INTEGRAL MOVEMENT SENSOR SWITCH.
	L6: 600 x 600 WHITE RECESSED FLAT PANEL TROFFER.
	L7: WHITE RECESSED AMENITY DOWNLIGHT.
	L8: NO LONGER REQUIRED.
	L9: WHITE RECESSED DALI DIMMABLE DOWNLIGHT.
	L10: 1200 LONG WALL MOUNTED BATTEN.
	CTX: DECORATIVE CATENARY LIGHTING SYSTEM TYPE x.
	FLx: DECORATIVE TREE FAIRY LIGHT SYSTEM TYPE x.
	SDL1: SURFACE CAN DOWNLIGHT.
	SDL2: SURFACE CAN DOWNLIGHT.
	SDL3: SURFACE DECORATIVE FITTING.
	SDL4: BLACK SURFACE CAN DOWNLIGHT.
	TRK1: TRACK LIGHT SYSTEM.
	HEC: CEILING MOUNTED HEATER, TYPE x.
	HEW: WALL MOUNTED HEATER.
	PL1: DECORATIVE PENDANT.
	PL2: DECORATIVE PENDANT.
	PL3: DECORATIVE PENDANT.
	PL4: NO LONGER REQUIRED.

LEGEND

	RDL1: DECORATIVE RECESSED DOWNLIGHT.
	RDL3: DECORATIVE WALL WASHER.
	RDL4: DECORATIVE RECESSED DOWNLIGHT.
	RDL5: BLACK DECORATIVE RECESSED DOWNLIGHT.
	STL1: DECORATIVE RECESSED BRICK LIGHT.
	UP1: INGROUND UP LIGHT.
	UP2: GARDEN STAKE LIGHT.
	S1: NO LONGER REQUIRED.
	S2: STAIR HANDRAIL LIGHTS.
	S3: STAIR HANDRAIL LIGHTS.
	S4: GAMING CEILING STRIP LIGHTS.
	S5: PUBLIC BAR REAR COUNTER STRIP LIGHTS.
	S6: STAIR HANDRAIL LIGHTS.
	S7: LOUNGE BAR STRIP LIGHTS.
	S8: SUNSET DISPLAY STRIP LIGHTS.
	S9: CASHIER REAR DISPLAY STRIP LIGHTS.
	S10: SUNSET BAR COUNTER STRIP LIGHT.
	S11: TOP DECK BAR REAR DISPLAY STRIP LIGHT.
	S12: AMENITY PELMET STRIP LIGHT.
	S13: PIZZA COUNTER STRIP LIGHT.
	S14: CONCRETE SEAT ROPE LIGHT.
	S15: CONCRETE SEAT ROPE LIGHT.
	S16: FUNCTION ROOM CEILING PELMET STRIP LIGHT.
	S17: GAMING BAR SKIRTING STRIP LIGHT.
	S18: SPORTS BAR OVERHEAD SHELIVING STRIP LIGHT.
	WL1: DECORATIVE WALL LIGHT.
	WL2: DECORATIVE WALL LIGHT.
	WL3: DECORATIVE WALL LIGHT.
	WL4: LOW LEVEL WALL UPLIGHT.
	WL5: VANITY WALL LIGHT.
	F1: CEILING FAN.
	L11: 70W CARPARK LIGHT MOUNTED ON A 9m POLE.
	L12: 50W CARPARK LIGHT MOUNTED ON A 9m POLE.
	L13: 50W CARPARK LIGHT MOUNTED ON A 8m POLE ON A CONCRETE BOLLARD.
	L14: 70W CARPARK LIGHT MOUNTED ON A 9m POLE.
	L15: 50W CARPARK LIGHT MOUNTED ON A 9m POLE.
	L16: 50W CARPARK LIGHT MOUNTED ON A 8m POLE ON A CONCRETE BOLLARD.
	L17: 50W CARPARK LIGHT MOUNTED ON A 9m POLE.

NOTE

ALL ELECTRICAL PENETRATIONS THROUGH THE ROOF SHEETING ARE TO BE IN LINE WITH THE STRUCTURAL OR MECHANICAL SERVICES PENETRATIONS TO AVOID DEDICATED FLASHINGS FOR THE ELECTRICAL SERVICES.