

1069

MINI AURA



SPECIFICATIONS:

1.9 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	Tilt 15°	Class I	IP67	CE	3 Year warranty	Made in Australia
--------	----------------------	---------------	----------	---------	------	----	--------------------	-------------------

CONSTRUCTION & DESIGN

- Inground LED tilt adjustable exterior uplighter
- Trim constructed in cast AISI 316 brushed stainless steel and body constructed in AISI 304 stainless steel and finished in black powdercoat paint
- 10mm clear toughened cool touch glass and durable silicone seals providing IP67 protection
- Plastic installation well included with each fitting to facilitate installation and maintenance

OPTICAL & THERMAL PERFORMANCE

- Optics and integral heatsink provides premium optical and thermal performance
- Efficient optical control available in various beam angles with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with an integral leading and trailing edge dimmable driver and long three core input cable 500m length
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz





TECHNICAL PERFORMANCE

- 8W or 13W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

CODE ORDERING GUIDE:

PRODUCT CODE / DIM CODE - COLOUR CODE


Example: 1069-SP-3K-8W-28 or 1069-SP-3K-8W/DALI-28

SYSTEM POWER	COLOUR TEMP.	 24° SP	 36° FL	 47° WFL	 55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT			
		PRODUCT CODE					SP	FL	WFL	VWFL
8W	3K	1069-SP-3K-8W	1069-FL-3K-8W	1069-WFL-3K-8W	-	828	616	643	660	-
	4K	1069-SP-4K-8W	1069-FL-4K-8W	1069-WFL-4K-8W	-	870	651	670	702	-
	5K	1069-SP-5K-8W	1069-FL-5K-8W	1069-WFL-5K-8W	-	845	635	663	680	-
13W	3K	1069-SP-3K-13W	1069-FL-3K-13W	-	1069-VWFL-3K-13W	1519	1171	1164	-	1144
	4K	1069-SP-4K-13W	1069-FL-4K-13W	-	1069-VWFL-4K-13W	1607	1229	1222	-	1204
	5K	1069-SP-5K-13W	1069-FL-5K-13W	-	1069-VWFL-5K-13W	1568	1199	1192	-	1175


INSTALLATION WELL

Installation well included

Nylon plastic well to facilitate installation & maintenance. Supplied with each fitting. Height of plastic well is 415mm and the diameter is 240mm. The luminaire must be mounted with suitable drainage as shown below.



243




154

DIM CODE


/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	x	x
	Leading & Trailing edge	Std	Std

COLOUR CODE

-28	Brushed StainlessSteel
-----	------------------------



177



200