

1463
1464

Vista



CONSTRUCTION & DESIGN

- LED exterior pole top luminaire
- Constructed with corrosion resistant die cast aluminium alloy and finished in textured black and textured silver durable powdercoated paint
- Diffuser is made from vandal proof and impact resistant polycarbonate
- Stainless steel screws and silicone seals provide IP65 weather protection
- Ideal for public areas, hotels, parks, gardens and pedestrian precincts

TECHNICAL PERFORMANCE


- 45W or 60W total system power consumption with overload and short circuit protection
- >65,000+ hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K, and 5K colour temperature with low colour shift over time
- Spigot size of Ø76mm

OPTICAL & THERMAL PERFORMANCE

- Components are mounted on custom designed aluminium and die cast housing for optimal heat sinking
- LED thermal management system incorporates both conduction and natural convection to transfer heat rapidly away from LED source
- Ultra low glare with symmetrical light distribution

ELECTRICAL SYSTEM

- Supplied completely assembled with integral non-dimmable driver
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz




SUITABLE FOR 76MM POLE DIAMETER

3K and 4K CRI >85	5K CRI >75			F		CE	IP65
----------------------	---------------	--	--	---	--	----	------

TOTAL SYSTEM POWER CONSUMPTION = 60W

CODE ORDERING GUIDE: PRODUCT CODE – COLOUR SUFFIX

Example: 1463-3K-07

WATTAGE	COLOUR TEMPERATURE	 WIDE BEAM ANGLE	HOT LED LUMENS
		PRODUCT CODES	
45W	3K	1463-3K	5340
	4K	1463-4K	5610
	5K	1463-5K	6269
60W	3K	1464-3K	7072
	4K	1464-4K	7436
	5K	1464-5K	7592

TRIM COLOUR OPTIONS: ADD SUFFIX AFTER THE CODE

-07  Textured Black-11  Textured Silver