

1373

RULLO



SPECIFICATIONS:

0.3 kg

 CRI 82+
3K and 4K

 CRI 70+
5K

Rot °180

Tilt 150°

SELV

IP54

CE

 3
Year warranty

Made in Australia

CONSTRUCTION & DESIGN

- Outdoor LED adjustable floodlight
- Constructed in machined aluminium alloy and finished in durable anodised coating
- Clear tempered glass lens with silicone seals and stainless steel exposed fasteners provide IP54 weather protection
- Integral constant current controller immune to voltage drop

OPTICAL & THERMAL PERFORMANCE

- Optics and integral heatsink provides premium optical and thermal performance
- Efficient optical control available various beam angles with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Input voltage 24V DC:** Connects to remote 24V DC power supply (TO BE ORDERED SEPARATELY)
- Supplied with 2m input cable
- Parallel connection

TECHNICAL PERFORMANCE

- 8W or 12W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

CODE ORDERING GUIDE:

PRODUCT CODE

COLOUR CODE

Example: 1373-SP-3K-8W-24V-08

SYSTEM POWER	COLOUR TEMP.	PRODUCT CODE			HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT		
		24° SP	36° FL	44° WFL		SP	FL	WFL
8W	3K	1373-SP-3K-8W-24V	1373-FL-3K-8W-24V	1373-WFL-3K-8W-24V	828	693	702	720
	4K	1373-SP-4K-8W-24V	1373-FL-4K-8W-24V	1373-WFL-4K-8W-24V	870	727	738	756
	5K	1373-SP-5K-8W-24V	1373-FL-5K-8W-24V	1373-WFL-5K-8W-24V	845	714	724	742
12W	3K	1373-SP-3K-12W-24V	1373-FL-3K-12W-24V	1373-WFL-3K-12W-24V	1519	944	957	980
	4K	1373-SP-4K-12W-24V	1373-FL-4K-12W-24V	1373-WFL-4K-12W-24V	1607	993	1007	1032
	5K	1373-SP-5K-12W-24V	1373-FL-5K-12W-24V	1373-WFL-5K-12W-24V	1568	973	987	1011

Ø72

131

79

74

DIM CODE		8W	12W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓
	Non-dimmable	Std	Std


COLOUR CODE

-08	Anodised Black
-13	Anodised Silver


ACCESSORIES: Add colour suffix after the code

373 -08 / -13	Ground spike constructed in aluminium alloy	330 200
374 -08 / -13	Surface mount base constructed in aluminium alloy	Ø50

WIRING DIAGRAM:



WIRING DIAGRAM FOR DALI OR 1-10V DIMMING:



WIRING DIAGRAM FOR SWITCH DIM:

