



Platinum Exit LED Quickfit Pictograph 1 Box Solution



- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type Emergency Lighting	Exit
Testing System	Single Point Unit
Operating Mode	Maintained
Operating Voltage	240 VAC
Rated Frequency	50 Hz
Power Consumption	3.2 W
Mounting	Surface - Universal
Viewing Distance	24 meters
LED Life	100,000 hours
Photometric Classification	C0:D3.2 C90:D3.2
Battery Type	LiFePO4
Height	214 mm
Width	72 mm
Depth	379 mm
Base Colour	White
Diffuser Colour	White on Green
Battery Replacement	0301302P
IP Rating	IP20
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: [Quickfit LED Exit Sign, LifePO4 Battery_Supplier Declaration of Conformity \(SDoC\)](#)

Installation Guide: -

User Manual: -

Manufacturer Datasheet: [Platinum Exit LED Quickfit_Manufacturer Datasheet](#)

Manufacturer Catalogue
& Product Selection: -

IP65 Weather Proof Kit to Suit Quickfit Series GRP Base with Polycarbonate Diffuser



Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type	Emergency Lighting	Diffusers and Wireguards
Rated Frequency	50 Hz	
Mounting	Surface - Ceiling	
IP Rating	IP65	
IK Rating	IK08	

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-