

1059

AURA



SPECIFICATIONS:

4.7 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	2 way tilt 5°	Class I	IP65	CE	5 Year warranty	Made in Australia
--------	----------------------	---------------	---------------	---------	------	----	--------------------	-------------------

CONSTRUCTION & DESIGN

- Inground LED adjustable exterior uplighter
- Trim constructed in cast AISI 316 brushed stainless steel and body constructed in AISI 304 stainless steel and finished in black powdercoat paint
- 10mm clear toughened cool touch glass and durable silicone seals providing IP65 protection
- Plastic installation well included with each fitting to facilitate installation and maintenance
- 2 way internal tilt adjustable light source

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control available in various beam angles with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with an integral leading and trailing edge dimmable driver and three core input cable - 500mm length
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz




TECHNICAL PERFORMANCE


- 22W or 28W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high Lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

CODE ORDERING GUIDE:

PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1059-SP-3K-22W-28 or 1059-SP-3K-22W/DALI-28

SYSTEM POWER	COLOUR TEMP.	 24° SP	 36° FL	 47° WFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT		
		PRODUCT CODE				SP	FL	WFL
22W	3K	1059-SP-3K-22W	1059-FL-3K-22W	1059-WFL-3K-22W	2414	1792	1782	1790
	4K	1059-SP-4K-22W	1059-FL-4K-22W	1059-WFL-4K-22W	2584	1855	1853	1862
	5K	1059-SP-5K-22W	1059-FL-5K-22W	1059-WFL-5K-22W	2520	1847	1837	1846
28W	3K	1059-SP-3K-28W	1059-FL-3K-28W	1059-WFL-3K-28W	3312	2459	2446	2420
	4K	1059-SP-4K-28W	1059-FL-4K-28W	1059-WFL-4K-28W	3480	2582	2564	2541
	5K	1059-SP-5K-28W	1059-FL-5K-28W	1059-WFL-5K-28W	3405	2535	2521	2494



260




350

INSTALLATION WELL


Installation well included

Nylon plastic well to facilitate installation & maintenance. Supplied with each fitting. Height of plastic well is 415mm and the diameter is 240mm. The luminaire must be mounted with suitable drainage as shown below.



415

240



DIM CODE

		22W	28W
/DALI	Dali Dimming / Switch Dim	✓	✓
	Leading & Trailing edge	Std	Std

COLOUR CODE

-28	Brushed Stainless Steel
-----	-------------------------

MAX
2000kg

A maximum trafficable load weight of 2000kg is allowed. Prolonged standing on floodlight when lit is not recommended.