

C2741a - GEEBUNG RSL


C2741a-0002(G).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION G - 13 OCTOBER 2023

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L1	28W 3000K LED	RECESSED 32 DEG BEAM DOWNLIGHT C/W REMOTE DRIVER	WHITE TRIM	GAMMA COBALT 1406-3K	A
L2	28W 3000K LED	RECESSED 32 DEG BEAM DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE TRIM	GAMMA COBALT 1406-3K	A
L3	8W 3000K LED	RECESSED DOWNLIGHT C/W REMOTE DALI DRIVER	WHITE	GAMMA ILLUMINATION MYLO 1004-WFL-3K-8W	A
L4	3000K LED	DECORATIVE 300 LONG TUBE PENDANT WITH THE SUSPENSION HEIGHT NOMINATED ON SITE BY THE ARCHITECT REMOTE DALI DIMMABLE DRIVER ALLOW TO INSTALL ALLOW A PC SUM FOR THE SUPPLY OF EACH L4 FITTING.	BRASS	ALLOW A PC SUM OF \$500.00 FOR THE SUPPLY OF EACH L4 FITTING	A
L5	3000K LED	DECORATIVE 600 LONG TUBE PENDANT WITH THE SUSPENSION HEIGHT NOMINATED ON SITE BY THE ARCHITECT REMOTE DALI DIMMABLE DRIVER ALLOW TO INSTALL ALLOW A PC SUM FOR THE SUPPLY OF EACH L5 FITTING.	BRASS	ALLOW A PC SUM OF \$500.00 FOR THE SUPPLY OF EACH L5 FITTING	A
L6	E27 2700K ROUND 240 VOLT LED 3 WATT	300 DIA DECORATIVE PENDANT WITH THE SUSPENSION HEIGHT NOMINATED ON SITE BY THE ARCHITECT	WHITE	ABOUT SPACE SKYBALL 300	A
L7	450LUMEN 2700K LED	SURFACE MOUNTED ADJUSTABLE DOWNLIGHT C/W REMOTE DALI DIMMABLE POWER SUPPLY IT IS ACCEPTABLE TO USE A SUITABLY SIZED SINGLE POWER SUPPLY / DALI CONTROLLER TO SUPPLY MULTIPLE L7 FITTINGS ON THE SAME CHANNEL. LOCATE THE POWER SUPPLY AND DALI CONTROLLER IN A CONCEALED ACCESSIBLE POSITION WITH THE LOCATION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	WHITE	NPA L-FX-SL-ARA-SP1301WM-12V-27K-D	A
L8	450LUMEN 2700K LED	COLUMN MOUNTED UP / DOWN LIGHT C/W REMOTE DALI DIMMABLE POWER SUPPLY IT IS ACCEPTABLE TO USE A SUITABLY SIZED SINGLE POWER SUPPLY / DALI CONTROLLER TO SUPPLY MULTIPLE L8 FITTINGS ON THE SAME CHANNEL. LOCATE THE POWER SUPPLY AND DALI CONTROLLER IN A CONCEALED ACCESSIBLE POSITION WITH THE LOCATION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	WHITE	NPA L-FX-SL-ARA-SP1303WM-12V-27K-D	A



C2741a - GEEBUNG RSL

C2741a-0002(G).xls

ELECTRICAL EQUIPMENT SCHEDULE


REVISION G - 13 OCTOBER 2023

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L9	450LUMEN 2700K LED	SURFACE MOUNTED ADJUSTABLE DOWNLIGHT C/W REMOTE DALI DIMMABLE POWER SUPPLY IT IS ACCEPTABLE TO USE A SUITABLY SIZED SINGLE POWER SUPPLY / DALI CONTROLLER TO SUPPLY MULTIPLE L9 FITTINGS ON THE SAME CHANNEL. LOCATE THE POWER SUPPLY AND DALI CONTROLLER IN A CONCEALED ACCESSIBLE POSITION WITH THE LOCATION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	WHITE	NPA L-FX-SL-ARA-SP1301WM-12V-27K-D	A
L10	NO LONGER REQUIRED				D
L11	NOT USED				A
L12	8W 3000K LED	IP65 ADJUSTABLE INGROUND UPLIGHT POSITIONED AS DIRECTED BY THE ARCHITECT ON SITE DRAIN EACH FITTINGS WELL TO STORM WATER. ENSURE THE TOP OF THE FITTING IS FLUSH WITH THE ADJACENT HARD FINISH IT IS ACCEPTABLE TO SUPPLY MULTIPLE L12 FITTINGS FROM A SUITABLE SIZED AND IP RATE CONCEALED REMOTE POWER SUPPLY	STAINLESS STEEL	GAMMA ILLUMINATION MINI AURA 1069-FL-3K-24V	A
L13	28W 4000K LED	IP65 ADJUSTABLE INGROUND UPLIGHT POSITIONED 300MM FROM THE CENTRE OF THE POLE TO UPLIGHT THE POLE AND FLAG THE L13 FITTINGS ARE TO BE WIRED BACK TO DRIVERS / CONTROL AS PER THE L13 LIGHTING CONTROL SCHEMATIC DRAIN EACH FITTINGS WELL TO STORM WATER. ENSURE THE TOP OF THE FITTING IS FLUSH WITH THE ADJACENT HARD FINISH	STAINLESS STEEL	GAMMA ILLUMINATION AURA 1059-SP-4K-28W	A
L14	45W 3000K LED	POLE MOUNTED AREA LIGHT ON A 4M HIGH 76OD POLE C/W RAG BOLT FOOTING.	BLACK FITTING AND POLE	GAMMA ILLUMINATION VISTA 1463-3K	A
L15	5W 3000K LED	IP65 ADJUSTABLE GARDEN STAKE LIGHT POSITIONED AS DIRECTED BY THE ARCHITECT ON SITE IT IS ACCEPTABLE TO SUPPLY MULTIPLE L15 FITTINGS FROM A SUITABLE SIZED AND IP RATE CONCEALED REMOTE POWER SUPPLY	BLACK	GAMMA ILLUMINATION RULLO 1373	A
L16	3000K 240VOLT GU10 LED 3WATT	NEW PENDANT FITTINGS MOUNTED OVER THE BAR COUNTER CONFIRM THE SUSPENSION HEIGHT ON SITE WITH THE ARCHITECT	GOLD JET BLACK	EST LIGHTING ODREY 1.2 287220GB0	A
L17	3NO 3000K 240V B22 LEDS 5 WATTS	REPLACE THE EXISTING POOL TABLE PENDANT LIGHT WITH A NEW THREE LAMP FITTING UTILISING THE EXISTING CIRCUIT AND CONTROL	BRIGHT SOLID BRASS	FAT SHACK VINTAGE P439-SML-BRSB	A

C2741a-0002(G).xls

Pages inc. any attach. 2 of 6



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au


C2741a - GEEBUNG RSL

C2741a-0002(G).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION G - 13 OCTOBER 2023

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L18	1250LUMEN +/- 10% 4000K LED	RECESSED 50 000 HOUR 55 DEG LED DOWN LIGHT C/W REMOTE 100 000 HOUR DRIVER. UTILISE THE EXISTING WELFARE OFFICE LIGHTING CIRCUIT TO SUPPLY THE L18 FITTINGS.	WHITE	FITTING SELECTION BY CONTRACTOR	B
L19	WALL MOUNTED ETERNAL FLAME TO BE SUPPLIED BY THE CLUB INSTALL AS PER THE ARCHITECTURAL WALL ELEVATION				C
L20	8W 3000K LED	RECESSED DOWNLIGHT C/W REMOTE DALI DRIVER	WHITE	GAMMA ILLUMINATION TO MATCH EXISTING CUTOUT	D
WL01	6W 3000K LED	DINING WALL LIGHT MOUNTED AS PER THE ELEVATION	PAINTED GOLD	ABOUT SPACE DARLA	A
WL02	3W 3000K 240V LED	DINING WALL LIGHT MOUNTED ON THE COLUMN CONFIRM THE MOUNTING HEIGHT ON SITE WITH THE ARCHITECT	BRASS	SPENCE & LYDA HANGING LAMP No 2	A
WL03	2W 3000K LED	WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL ELEVATION	BRASS	ABOUT SPACE FORTE V12	A
S1	WARM WHITE LED	REMOVE THE EXISTING EXPOSED NEON AND PROVIDE A SURFACE MOUNTED HORIZONTAL LED STRIP WITHIN A ALUMINIUM EXTRUSION SCREW FIXED IN PLACE AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIPS WITH A COMMON REMOTE DEDICATED 240-12V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER 20M OF STRIP	NATURAL	NEON PRODUCTS AUSTRALIA LF-DFB-WW-300-12 + PR-LIN172153-F	A
S2	WARM WHITE LED	MULTIPLE HORIZONTAL LED STRIPS WITHIN RECESSED ALUMINIUM EXTRUSIONS SCREW FIXED IN PLACE WITHIN THE JOINERY AS PER THE ARCHITECTURAL DETAIL QUANTITIES AS PER THE ELEVATION PROVIDE THE STRIPS WITH A COMMON REMOTE DEDICATED 240-12V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER 20M OF STRIP	NATURAL	NEON PRODUCTS AUSTRALIA LF-DFB-WW-300-12 + PR-LIN172153-F	A
S3	12W/M 2700K LED	MULTIPLE RECESSED FLEXIBLE LED ROPE FLEX SCREW FIXED IN PLACE WITHIN THE COUNTER PELMET S AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP	WHITE	NPA L-NF-GLOW-VWW + POWER SUPPLY & DALI CONTROLLER	A




C2741a - GEEBUNG RSL

C2741a-0002(G).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION G - 13 OCTOBER 2023

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
S4	12W/M 2700K LED	MULTIPLE RECESSED FLEXIBLE LED ROPE FLEX SCREW FIXED IN PLACE WITHIN THE WALL JOINERY AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP	WHITE	NPA L-NF-GLOW-VWW + POWER SUPPLY & DALI CONTROLLER	A
S5	12W/M 2700K LED	RECESSED FLEXIBLE LED ROPE FLEX SCREW FIXED IN PLACE BEHIND THE MIRROR AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP	WHITE	NPA L-NF-GLOW-VWW + POWER SUPPLY & DALI CONTROLLER	A
S6	EXISTING LED STRIP TO BE REUSED				C
E1	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40.	WHITE	STANILITE SF1LEDP LITHIUM BATTERY	A
E2	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40. MOUNT THE FITTING IN A SURFACE MOUNTED CAN	WHITE	STANILITE SF1LEDP LITHIUM BATTERY	A
E3	NOT USED				A
E4	LED	EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-D3.2 - C90-E2.	WHITE LOGO GREEN BACKGROUND WHITE BODY	STANILITE PLQLEDP LITHIUM BATTERY	A
E5	LED	EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN AND A IP56 HOUSING CEILING OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-D3.2 - C90-E2.	WHITE LOGO GREEN BACKGROUND WHITE BODY	STANILITE LED LEGEND QUICKFIT PQFLEDP WEATHERPROOF PWQFKITPOLY	A
EMERGENCY PACK		LIGHT FITTINGS THAT ARE DESIGNATED AS BEING PROVIDED WITH AN EMERGENCY PACK ARE TO BE PROVIDED WITH AN INTEGRAL AS2293 EMERGENCY PACK. THE FITTINGS ARE TO BE NON MAINTAINED WITH ALL LAMPS SWITCHED AS PER THE LIGHTING CONTROL FOR THAT SPACE UNLESS NOTED OTHERWISE. REFER TO THE SPECIFICATION FOR FURTHER DETAILS OF THE CONFIGURATION AND SWITCHING OF EMERGENCY LIGHTS.			A




C2741a - GEEBUNG RSL

C2741a-0002(G).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION G - 13 OCTOBER 2023

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
PROXIMITY DETECTOR SWITCH (PD)		ADJUSTABLE FLUSH RECESSED 360 DEGREE TRIPLE PYRO PIR PRESENCE DETECTOR TO OPERATE THE ASSOCIATED LIGHTS FOR A PRE-SET AMOUNT OF TIME. ADJUST THE TIME AND SENSITIVITY ON SITE AS DIRECTED BY THE ENGINEER.	WHITE	CLIPSAL. SELECTION BY THE CONTRACTOR. SUBMIT DETAILS OF THE PROXIMITY DETECTOR SWITCH FOR APPROVAL PRIOR TO ORDERING	A
ONE WAY SWITCH		ONE WAY 20A SWITCH TO CONTROL THE HEAT LAMPS MOUNTED AT 1000 AFFL	WHITE	CLIPSAL C2000	A
SWITCH PANEL (SP)		LIGHTING CONTROL 6 BUTTON / LCD SCREEN MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE. CONNECTED TO THE ASSOCIATED DISTRIBUTION BOARDS DYNALITE NETWORK	WHITE	PHILIPS DYNALITE PADPA	A
FIRE INDICATOR PANEL (FIP)		AS 1670 COMPLAINT FIRE INDICATOR PANEL TO BE UPGRADED AS NECESSARY TO ACCOMMODATE THE FIRE ALARM SYSTEM MODIFICATIONS			A
HEATER TYPE 1 (H1)		CEILING MOUNTED DECORATIVE HEAT LAMP PENDANT C/W LAMP. CONFIRM THE SUSPENSION HEIGHT ON SITE WITH THE ARCHITECT	ANTIQUE BRASS	HATCO DL-1700-AS	A
HEATER TYPE (H2)		CONNECT THE HEAT LAMPS PROVIDED AS PART OF THE KITCHEN SERVICES			A
SINGLE POWER OUTLET		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE	CLIPSAL C2000 SERIES	A
SINGLE POWER OUTLET FOR AUTO DOOR (AD)		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED WITHIN THE AUTO DOOR MULLION. RATING 10A U.N.O.	WHITE	CLIPSAL C2000 SERIES	A
DOUBLE POWER OUTLET		DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE	CLIPSAL C2000 SERIES	A
DOUBLE POWER OUTLET USB		DOUBLE POWER OUTLET C/W INTEGRAL 5V 2 X 2.4A AND 1 x 3A TYPE C USB CHARGER WITH CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND. CONFIRM THE MOUNTING HEIGHT ON SITE WITH THE ARCHITECT. RATING 10A U.N.O.	WHITE	4CABLING 040.000.0117	G
WEATHERPROOF POWER OUTLET (WP)		IP54 WEATHERPROOF SINGLE / DOUBLE POWER OUTLET AS NOTED ON DRAWING C/W COVER FLAP OVER SOCKET. MOUNT AT MINIMUM 1100mm AFFL U.N.O. RATING 10A U.N.O.	-	CLIPSAL WSCF227F	A



C2741a - GEEBUNG RSL

C2741a-0002(G).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION G - 13 OCTOBER 2023

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
SPECIAL PURPOSE OUTLET		SPECIAL PURPOSE OUTLET TYPE AS NOTED. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.			A
HAND DRYER CONNECTION (HD)		20A ISOLATING SWITCH WALL MOUNTED AT 2400mm AFFL AND CONNECTED TO THE HAND DRYER UNIT AS PER DETAIL.		CLIPSAL ICONIC SERIES 30USM	A
SINGLE-PHASE ISOLATOR		SINGLE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT20	A
THREE-PHASE ISOLATOR		THREE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT35	A
DB-M1		MODIFY THE EXISTING DISTRIBUTION BOARD AS NECESSARY SUCH THAT IT ACCOMMODATES THE CIRCUITS AND CONTROLS AS NOTED. RECONNECT ALL OF THE EXISTING CIRCUITS THAT REMAIN WITH NEW AS3000 COMPLIANT SWITCHGEAR.			F
DB-M2		MODIFY THE EXISTING DISTRIBUTION BOARD AS NECESSARY SUCH THAT IT ACCOMMODATES THE CIRCUITS AND CONTROLS AS NOTED. RECONNECT ALL OF THE EXISTING CIRCUITS THAT REMAIN WITH NEW AS3000 COMPLIANT SWITCHGEAR.			F
DB-2		NO LONGER REQUIRED			F
DB-6		PROVIDE DB-4 AS A NEW DISTRIBUTION BOARD AS PER THE DB-6 SCHEDULE. PROVIDE A SHOP DRAWING FOR APPROVAL. PROVIDE THE DISTRIBUTION BOARD WITH AN ACCURATE CIRCUIT SCHEDULE INCLUDING THE USE AND LOCATION OF EACH CIRCUIT.			F
MSB		MAIN SWITCHBOARD TO BE PROVIDED WITH A NEW 160A MCCB ON THE NON GENERATOR CHASSIS TO SUPPLY DB-6. UPDATE THE LABELLING TO ACCURATELY REFLECT THE SWITCHGEAR USE.			A
COMMUNICATIONS OUTLET		RJ45 CAT-6 COMMUNICATIONS OUTLET, CABLED BACK TO THE EXISTING LEVEL 1 COMMUNICATIONS RACK WITH NEW CAT 6 PATCH PANELS AS REQUIRED VIA 4-PAIR CAT-6 UTP CABLE. MOUNT UP TO 3 RJ45 OUTLETS PER MULTI-GANG FACEPLATE WITH SEPARATE PERMANENT LABELLING FOR EACH OUTLET. MOUNT AT 300 AFFL UNLESS NOTED OTHERWISE	WHITE	CLIPSAL "C2000 SERIES"	A