

1192

ATRIA



SPECIFICATIONS:



CONSTRUCTION & DESIGN

- Recessed LED fixed downlight with frosted diffuser
- Constructed in die cast aluminium alloy and finished in durable polyester powdercoat paint
- Recessed primary optics and secondary polycarbonate diffuser gives a symmetrical wide beam distribution with high lumen output
- Silicone gasket seal on trim providing penetration protection
- Installation springs suitable for ceiling thickness up to 20mm

OPTICAL & THERMAL PERFORMANCE

- Reflector, diffuser and efficient heatsink provides premium optical and thermal performance
- Efficient optical control in wide beam angle and no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with a remote leading and trailing edge mains dimmable driver, which is compatible with a range of dimming systems
- All drivers come with a quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 13W or 22W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

CODE ORDERING GUIDE:


PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1192-3K-13W-01 or 1192-3K-13W/DALI-01

SYSTEM POWER	COLOUR TEMP.	62° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		62°
13W	3K	1192-3K-13W	1519	1016
	4K	1192-4K-13W	1607	1071
	5K	1192-5K-13W	1570	1047
22W	3K	1192-3K-22W	2414	1595
	4K	1192-4K-22W	2584	1693
	5K	1192-5K-22W	2526	1655

DIM CODE		13W	22W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓
	Leading & Trailing edge	Std	Std

COLOUR CODE		
-01		Satin White
-06		Matte Black



TOTALLY SEALED UNIT WITH
CABLE GLAND FITTED FOR IP65
PROTECTION

