

1340

1341

1342

ALTUS



UNIQUE SQUARE
DOUBLE BATWING
LIGHT OUTPUT

SPECIFICATIONS:



3.3 kg



3K and 4K



5K



Class I



IK10



IP65



CE



5

Year warranty



Made in Australia

CONSTRUCTION & DESIGN

- LED exterior adjustable floodlight
- Constructed in pressure die cast and extruded aluminium alloy and finished in durable polyester powdercoat paint
- Secure tilt adjustable mechanism for reliable and accurate alignment
- Tempered glass cover, stainless steel exposed fasteners and silicone seals provide IP65 weather protection

OPTICAL & THERMAL PERFORMANCE

- Unique square double batwing light output
- LED thermal management system incorporates both conduction and natural convection to transfer heat rapidly away from LED source
- Efficient optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with an integral non-dimmable driver and 200mm input cable
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 28W, 45W or 60W total system power consumption with overload and short circuit protection
- >150,000+ hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time


CODE ORDERING GUIDE:

PRODUCT CODE

/ DIM CODE


- COLOUR CODE

Example: 1340-3K-28W-03 or 1340-3K-28W/DALI-03

SYSTEM POWER	COLOUR TEMP.	 65x65° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		65x65°
28W	3K	1340-3K-28W	3213	2534
	4K	1340-4K-28W	3380	2661
	5K	1340-5K-28W	3310	2612
45W	3K	1341-3K-45W	5340	4402
	4K	1341-4K-45W	5610	4622
	5K	1341-5K-45W	5455	4489
60W	3K	1342-3K-60W	7605	5745
	4K	1342-4K-60W	8010	6032
	5K	1342-5K-60W	7780	5859

DIM CODE		28W	45W	60W
/DALI	Dali Dimming / Switch Dim	✓	✓	x
/DSI	Digital Dimming	x	x	x
/AD	Analogue Dimming 1-10V	x	x	x
/DIM	Leading & Trailing edge	Std	x	x
	Non-dimmable	x	Std	Std

COLOUR CODE		
-03		Textured White
-07		Textured Black
-11		Textured Silver



SECURE TILT ADJUSTABLE MECHANISM FOR RELIABLE AND ACCURATE ALIGNMENT

