

1410

CORBEL



## SPECIFICATIONS:

0.4 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	105	Tilt 35°	SELV	IP54	CE	Available	5 Year warranty	Made in Australia
--------	----------------------	---------------	-----	----------	------	------	----	-----------	--------------------	-------------------

## CONSTRUCTION &amp; DESIGN

- Recessed LED adjustable downlight
- Constructed in die cast aluminium alloy and finished in durable polyester powdercoat paint
- Low profile adjustable LED downlight with high lumen output
- Clear tempered glass front

## OPTICAL &amp; THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare

## ELECTRICAL SYSTEM

- Supplied standard with a remote leading and trailing edge mains dimmable driver, which is compatible with a range of dimming systems
- All drivers come with a quick connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

## TECHNICAL PERFORMANCE


- 8W or 13W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

## CODE ORDERING GUIDE:

PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1410-3K-8W-01 or 1410-3K-8W/DALI-01

SYSTEM POWER	COLOUR TEMP.	41° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		41°
8W	3K	1410-3K-8W	828	614
	4K	1410-4K-8W	870	654
	5K	1410-5K-8W	888	633
13W	3K	1410-3K-13W	1519	1115
	4K	1410-4K-13W	1607	1174
	5K	1410-5K-13W	1646	1150



DIM CODE		8W	13W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓
	Leading & Trailing edge	Std	Std

COLOUR CODE		
-01		Satin White
-06		Matte Black

## OVERALL VIEW

