



WSF226/20 Flush Switch, 1 Gang, 250VAC, 20A, IP66, Resistant Grey

Catalogue Number: [WSF226/20](#)

Flush Switches - Weather Protected, Flush Switches - Wsf Series - Weathershield - IP66, Shallow wall box and shroud for 84mm centre mounting accessory installation, Switch 1 Gang 250V 20A - standard size.

Already a Member?

[Login to view trade prices](#)

Not a Member?

[Register Now](#)

WSF226/20 Flush Switch, 1 Gang, 250VAC, 20A, IP66, Resistant Grey

Clipsal has developed the weathershield® range – perfect for use in wineries, factories, exterior walls, on illuminated signs and around swimming pools. Anywhere switchgear needs protection from the elements

If LED indicators are required, the 56LEDK1 can be added by the installer.

Edition 92 Trade Product Guide Page # 92

Key Features

- 1 gang
- M100 rating
- Weather protected switch

- Outdoor lighting, Illuminated signs
- 84 mm mounting centre
- With looping terminal
- Standard size

Product Specifications and Characteristics (ETIM Industrial Standard)

These specifications and characteristics outline physical, mechanical, electrical details.

Type	Value
Brand Name	Clipsal
Sub Brand	Weathershield, Series WSF
Wiring system	One-way/Two-way Switch
Method of operation	
Assembly arrangement	Basic element with full cover plate
Push button switch	
Number of rockers	
Mounting method	Flush mounted
Type of fastening	Mounting with screw
Material	
Material quality	
Halogen free	
Surface treatment	
Type of surface	Brilliant
Colour	Resistant grey
RAL-number (akin)	
Label space/information surface	
Illumination	Without illumination
Suitable for degree of protection (IP)	IP66
Nominal voltage	250 VAC
Switching current	20 A
Switching current for fluorescent lamps	AX
Feedback-signal contact	
Washing machine switch	
Number of Poles	