

1338

1339

1539

DOCK BOX



SPECIFICATIONS:



CONSTRUCTION & DESIGN

- Surface mounted LED exterior wall light
- Constructed in pressure die cast aluminium alloy and finished in durable powdercoat paint
- High performance fixed wall luminaire with forward throw optics providing optimal and uniform light output with low power consumption
- Prismatic tempered glass cover silicone housing seals with 4 cable and conduit entry points and stainless steel fasteners provide IP65 weather protection

OPTICAL & THERMAL PERFORMANCE

- LED thermal management incorporates both conduction and natural convection to transfer heat rapidly away from LED source to achieve maximum life of LED

ELECTRICAL SYSTEM

- Supplied standard with an integral driver and terminal block (refer to dimming options table)
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 28W, 42W or 60W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

CODE ORDERING GUIDE: PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1338-3K-28W-07 or 1338-3K-28W/DALI-07

SYSTEM POWER	COLOUR TEMP.	90x115° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
				90x115°
28W	3K	1338-3K-28W	3312	1912
	4K	1338-4K-28W	3480	2008
	5K	1338-5K-28W	3405	1971
42W	3K	1339-3K-42W	4699	2739
	4K	1339-4K-42W	4937	2876
	5K	1339-5K-42W	4846	2823
60W	3K	1539-3K-60W	7605	3824
	4K	1539-4K-60W	8010	4015
	5K	1539-5K-60W	7780	3942

DIM CODE		28W	42W	60W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓	✓
/DIM	Leading & Trailing edge	Std	✓	x
	Non-dimmable	x	Std	Std

COLOUR CODE	
-07	Textured Black

