

CLEVERTRONICS L10 CLEVERFIT EXIT



PRODUCT INFORMATION

Part Number	LCFLED
MIC	AUA01310220001
Description	L10 Lithium Nanophosphate Cleverfit Emergency Exit, Enabled with Clevertest Plus
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	355mm x 215mm x 80mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 4.5 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E2 C ₉₀ =E2
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY:L10 3.3V 2.5AH 390mm lead,noBRKT
8002321	PCA: LCFLED CT10164-L6 6C70 CTP DALI-COMP ZW AU
8002430	PCA:Duris P5 6 LED Strip.L10,#CT10166-D1

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order