



# ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: [www.edg.net.au](http://www.edg.net.au) Email: [brisbane@edg.net.au](mailto:brisbane@edg.net.au)

C3546a - BLUE FIN FISHING CLUB, INALA - STAGE 2


C3546a-0002(D).xls

## ELECTRICAL EQUIPMENT SCHEDULE

REVISION D - 08 JULY 2025

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK  
[www.edg.net.au/Links/Lighting.htm](http://www.edg.net.au/Links/Lighting.htm)

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L1	3000K LED	LED STRIP LIGHT MOUNTED IN THE PLANTER BASE AS PER THE ARCHITECTURAL DETAIL PROVIDE THE L1 STRIP WITH A COMMON REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP LOCATE THE POWER SUPPLY / DALI INTERFACE IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NA	NPA L-NF-GLOW-WWW + POWER SUPPLY & DALI CONTROLLER	A
L2	3000K LED	LED STRIP LIGHT MOUNTED IN THE PLANTER BASE AS PER THE ARCHITECTURAL DETAIL PROVIDE THE L2 STRIP WITH A COMMON REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP LOCATE THE POWER SUPPLY / DALI INTERFACE IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NA	NPA L-NF-GLOW-WWW + POWER SUPPLY & DALI CONTROLLER	A
L3	8W 3000K LED	RECESSED ADJUSTABLE DOWNLIGHT C/W REMOTE DRIVER	WHITE	GAMMA ILLUMINATION MYLO 1004-VWFL-3K-8W	A
L4	13W 3000K LED	RECESSED ADJUSTABLE DOWNLIGHT C/W REMOTE DRIVER	WHITE	GAMMA ILLUMINATION MYLO 1004-VWFL-3K-13W	A
L5	13W 3000K LED	RECESSED ADJUSTABLE DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION MYLO 1004-VWFL-3K-13W DALI	A
L6	3000K LED	LED STRIP LIGHT MOUNTED IN THE JOINERY SKIRTING AS PER THE ARCHITECTURAL DETAIL PROVIDE THE L6 STRIP WITH A COMMON REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP LOCATE THE POWER SUPPLY / DALI INTERFACE IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NA	NPA L-NF-GLOW-WWW + POWER SUPPLY & DALI CONTROLLER	A
L7	CONNECT THE LIGHTS SUPPLIED AS PART OF THE MIRROR TO THE ROOM LIGHTING.				C
L8	CONNECT THE LIGHTS SUPPLIED AS PART OF THE MIRROR TO THE ROOM LIGHTING.				C



# ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: [www.edg.net.au](http://www.edg.net.au) Email: [brisbane@edg.net.au](mailto:brisbane@edg.net.au)

C3546a - BLUE FIN FISHING CLUB, INALA - STAGE 2

C3546a-0002(D).xls

## ELECTRICAL EQUIPMENT SCHEDULE

REVISION D - 08 JULY 2025

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK  
[www.edg.net.au/Links/Lighting.htm](http://www.edg.net.au/Links/Lighting.htm)

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L9	3000K LED	LED STRIP LIGHT MOUNTED IN THE SUSPENDED BULKHEAD AS PER THE ARCHITECTURAL DETAIL PROVIDE THE L10 STRIP WITH A COMMON REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP LOCATE THE POWER SUPPLY / DALI INTERFACE IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NA	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A
L10	3000K LED	REPLACE THE EXISTING CEILING COFFER STRIP LIGHT WITH LED STRIP LIGHT PROVIDE THE L10 STRIP WITH A COMMON REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP LOCATE THE POWER SUPPLY / DALI INTERFACE IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NA	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	B
L11	28W 3000K LED	REPLACE THE EXISTING DOWNLIGHT WITH A RECESSED ADJUSTABLE DOWNLIGHT C/W REMOTE DRIVER PROVIDE A TRIM KIT AS NECESSARY TO ACCOMMODATE THE EXISTING CUTOFF IF NEEDED	WHITE	GAMMA ILLUMINATION ARIA 1427-3K-28W	B
L12	28W 3000K LED	NEW RECESSED ADJUSTABLE DOWNLIGHT C/W REMOTE DRIVER AND A TRIM KIT MATCHING THAT PROVIDED WITH THE L11 FITTINGS	WHITE	GAMMA ILLUMINATION ARIA 1427-3K-28W	B
L13	3000K LED	LED STRIP LIGHT MOUNTED IN THE JOINERY COUNTER PELMET AS PER THE ARCHITECTURAL DETAIL PROVIDE THE L13 STRIP WITH A COMMON REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP LOCATE THE POWER SUPPLY / DALI INTERFACE IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NA	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	B
PL1	3000K LED	1200 DIA CEILING MOUNTED FITTING C/W FIVE DROPPERS AND A REMOTE DALI DIMMABLE DRIVER ALLOW TO ASSEMBLE AND INSTALL	NA	ALLOW A PC SUM OF \$6,600.00 PLUS GST FOR THE SUPPLY OF EACH PL1 FITTING	A
E1	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D63 - C90-D63.	WHITE UNLESS NOTED AS BLACK (BK)	CLEVERTRONICS LLIFE	A



# ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: [www.edg.net.au](http://www.edg.net.au) Email: [brisbane@edg.net.au](mailto:brisbane@edg.net.au)

C3546a - BLUE FIN FISHING CLUB, INALA - STAGE 2

C3546a-0002(D).xls

## ELECTRICAL EQUIPMENT SCHEDULE

REVISION D - 08 JULY 2025

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK  
[www.edg.net.au/Links/Lighting.htm](http://www.edg.net.au/Links/Lighting.htm)

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
PROXIMITY DETECTOR SWITCH (PD)		ADJUSTABLE FLUSH RECESSED 360 DEGREE PIR PRESENCE DETECTOR TO OPERATE THE ASSOCIATED LIGHTS FOR A PRE-SET AMOUNT OF TIME. ADJUST THE TIME AND SENSITIVITY ON SITE AS DIRECTED BY THE ENGINEER. SUBMIT DETAILS OF THE MOVEMENT DETECTOR SWITCH FOR APPROVAL PRIOR TO ORDERING	WHITE	CLIPSAL	A
DOUBLE POWER OUTLET		DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK) OR GOLD (GD)	CLIPSAL C2000 SERIES	D
DOUBLE POWER OUTLET (M)		DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT IN THE VOID BEHIND THE MIRROR. COORDINATE THE POSITION WITH EH HAND DRYER AND SOAP DISPENSER RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
DOUBLE POWER OUTLET (USB)		DOUBLE POWER OUTLET C/W USB A AND USB C CHARGER, CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT ON THE JOINERY AS PER THE ARCHITECTURAL DETAIL.	WHITE UNLESS NOTED AS BLACK (BK) OR GOLD (GD)	CLIPSAL C2000 SERIES FACEPLATE	D
HAND DRYER CONNECTION (HD)		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND FOR THE HAND DRYER MOUNT THE GPO AS PER THE ARCHITECTURAL DETAIL	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
DB-T		DISTRIBUTION BOARD DB-T TO BE PROVIDED WITH THE ADDITIONAL SWITCHGEAR AND CRESTRON CONTROLS TO ACCOMMODATE THE CIRCUITS AND LIGHTING CONTROL AS PER THE NOTES. UPDATE THE SCHEDULE AT PRACTICAL COMPLETION.			A
MSB		MAIN SWITCHBOARD TO REMAIN AS IS			A
COMMUNICATIONS RACK (CR-A)		EXISTING COMMUNICATIONS RACK.. PROVIDE ADDITIONAL PATCH PANELS TO MATCH THE EXISTING AS NECESSARY TO ACCOMMODATE THE ADDITIONAL COMMUNICATIONS OUTLETS. UPDATE THE PATCH PANEL LABELLING PRIOR TO PRACTICAL COMPLETION.			A
COMMUNICATIONS OUTLET		RJ45 CAT-6 COMMUNICATIONS OUTLET, CABLED BACK TO CAT 6 PATCH PANELS IN RACK CR-A VIA 4-PAIR CAT-6 UTP CABLE. MOUNT UP TO 3 RJ45 OUTLETS PER MULTI-GANG FACEPLATE WITH SEPARATE PERMANENT LABELLING FOR EACH OUTLET. MOUNT AT 300 AFFL UNLESS NOTED OTHERWISE	WHITE UNLESS NOTED AS BLACK (BK) OR GOLD (GD)	CLIPSAL C2000 SERIES	D
FIRE INDICATOR PANEL (FIP)		EXISTING FIRE INDICATOR PANEL TO BE UPGRADED AS NECESSARY TO ACCOMMODATE THE WORKS.			A



# ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: [www.edg.net.au](http://www.edg.net.au) Email: [brisbane@edg.net.au](mailto:brisbane@edg.net.au)

C3546a - BLUE FIN FISHING CLUB, INALA - STAGE 2

C3546a-0002(D).xls

## ELECTRICAL EQUIPMENT SCHEDULE

REVISION D - 08 JULY 2025

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK  
[www.edg.net.au/Links/Lighting.htm](http://www.edg.net.au/Links/Lighting.htm)

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
FIRE EVACUATION SPEAKER		RECESSED 5W TWO-TONE 8-INCH CONE ALERT AND EVACUATION SPEAKER TO AS1670.1 C/W 100V MULTI-TAP TRANSFORMER AND FLUSH GRILLE PAINTED OUT TO MATCH THE CEILING. (SM) DENOTES TO BE SURFACE MOUNT. WHITE UNLESS NOTED AS BLACK.			A
SMOKE DETECTOR		SURFACE MOUNTED SMOKE DETECTOR TO AS1670. WHITE UNLESS NOTED AS BLACK.			A
AUTO DOOR EXIT PUSH BUTTON (PB1)		BLANK FACEPLATE C/W RECESSED DEEP WALL BOX AND A CONCEALED 32 DIA CONDUIT FROM THE WALL BOX TO THE AUTO DOOR MOTOR / CONTROLLER (DM1) MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL C2000 SERIES FACEPLATE	C
AUTO DOOR ENTRY PUSH BUTTON (PB2)		BLANK FACEPLATE C/W RECESSED DEEP WALL BOX AND A CONCEALED 32 DIA CONDUIT FROM THE WALL BOX TO THE AUTO DOOR MOTOR / CONTROLLER (DM1) MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL C2000 SERIES FACEPLATE	C
AUTO DOOR MOTOR / CONTROLLER (DM1)		SINGLE 10 AMP POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE MOUNTED AT HIGH LEVEL IN A CONCEALED POSITION FOR THE AUTO DOOR MOTOR / CONTROLLER AS DIRECTED / COORDINATED WITH BY THE AUTO DOOR SUPPLIER ON SITE	WHITE	CLIPSAL C2000 SERIES FACEPLATE	C