



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3604a - 25 SOUTH PINE ROAD, BRENDALE

C3604a-0002(A).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION A - 18 AUGUST 2025

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L1	40W 4000K LED	WALL MOUNTED 1200 LONG IP65 BATTEN .	NA	RAPID LED R3540-TRI	A
L2	40W 4000K LED	SURFACE MOUNTED 1200 LONG IP65 BATTEN C/W NON MAINTAINED UNSWITCHED AS2293 EMERGENCY PACK. THIS FITTING IS UNSWITCHED IS TO ONLY OPERATE ON MAIN FAILURE.	NA	RAPID LED R3540-EM-TRI	A
L3	200W 4000K LED	HIGH BAY PENDANT C/W INTEGRAL DRIVER	BLACK	SAL SHB23MP200TC-200-4000K	A
L4	13W 4000K LED	RECESSED DOWNLIGHT	WHITE TRIM	RAPID LED R1055-WH-TRI	A
L5	36W 4000K LED	600 X 600 SURFACE MOUNTED LED PANEL LIGHT	WHITE	RAPID LED R3205-TRI-SM	A
F1	4900 DIA 3 PHASE CEILING FAN C/W A STANDARD WIRED CONTROLLER MOUNTED ADJACENT THE LIGHTING CONTROL SPL. PROVIDE ALL NECESSARY STRUCTURAL SUPPORTS TO MOUNT THE FAN.		NA	BIGG ASS 4.9M DIA POWER FOIL C/W STANDARD WIRED CONTROLLER	A
E1	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40.	WHITE	CLEVERTRONICS CLIFE	A
E2	LED	EXIT LIGHT: MAINTAINED 40M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING SURFACE MOUNT OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-D8 - C90-E3.2.	WHITE	CLEVERTRONICS CJELED-40	A
EX	LED	EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING SURFACE MOUNT OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-E2 - C90-E2.	WHITE	CLEVERTRONICS CCFLED	A
CONDUIT ACCESS POINT (A1)		PROVIDE A 63 DIA POWER CONDUIT AND A 25 DIA COMMUNICATIONS CONDUIT FROM THE EXTERNAL EV CHARGER POSITION TO THE EVDB FOR USE BY THE FITOUT CONTRACTOR.			A



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3604a - 25 SOUTH PINE ROAD, BRENDAL

C3604a-0002(A).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION A - 18 AUGUST 2025

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
PROXIMITY DETECTOR SWITCH (PD)		ADJUSTABLE FLUSH RECESSED 360 DEGREE PIR PRESENCE DETECTOR TO OPERATE THE ASSOCIATED LIGHTS FOR A PRE-SET AMOUNT OF TIME. ADJUST THE TIME AND SENSITIVITY ON SITE AS DIRECTED BY THE ENGINEER. SUBMIT DETAILS OF THE MOVEMENT DETECTOR SWITCH FOR APPROVAL PRIOR TO ORDERING	WHITE	CLIPSAL	A
ONE-WAY LIGHT SWITCH		ONE-WAY LIGHT SWITCH C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL C2000 SERIES 30USM	A
ONE-WAY WEATHERPROOF LIGHT SWITCH (IP56)		IP56 ONE-WAY / TWO-WAY AS NOTED ON DRAWING LIGHT SWITCH C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED AT 1100mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL "56 SERIES"	A
LIGHTING CONTROL SWITCH PANEL (SP1)		MULTI GANG LIGHT SWITCH PANEL WITH UP TO FOUR SWITCHES PER FACEPLATE. MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL C2000 SERIES 30USM	A
SINGLE POWER OUTLET		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE	CLIPSAL C2000 SERIES	A
DOUBLE POWER OUTLET		DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE	CLIPSAL C2000 SERIES	A
15 AMP POWER OUTLET (15A)		15AMP SINGLE PHASE IP66 WEATHERPROOF SINGLE POWER OUTLET. MOUNTED AT 1000mm AFFL	HEAVY DUTY GREY	CLIPSAL 56 SERIES	A
3 PHASE POWER OUTLET (3PH)		20AMP THREE PHASE IP66 WEATHERPROOF SINGLE POWER OUTLET. MOUNTED AT 1000mm AFFL	HEAVY DUTY GREY	CLIPSAL 56 SERIES	A
SINGLE-PHASE ISOLATOR		SINGLE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT20	A
THREE-PHASE ISOLATOR		THREE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT35	A
DB-1		NEW WAREHOUSE DISTRIBUTION BOARD 1. REFER TO THE NOTES AND DB-1 SCHEDULE FOR ADDITIONAL REQUIREMENTS.			A



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3604a - 25 SOUTH PINE ROAD, BRENDAL

C3604a-0002(A).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION A - 18 AUGUST 2025

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
DB-2		NEW WAREHOUSE DISTRIBUTION BOARD 2. REFER TO THE NOTES AND DB-2 SCHEDULE FOR ADDITIONAL REQUIREMENTS.			A
DB-3		NEW WAREHOUSE DISTRIBUTION BOARD 3. REFER TO THE NOTES AND DB-3 SCHEDULE FOR ADDITIONAL REQUIREMENTS.			A
DB-A		NEW WAREHOUSE MAIN DISTRIBUTION BOARD. REFER TO THE NOTES AND POWER SCHEMATICS FOR ADDITIONAL REQUIREMENTS.			A
EV-DB		NEW EV CHARGING DB. REFER TO THE NOTES FOR ADDITIONAL REQUIREMENTS.			A
MSB		EXISTING MAIN SWITCHBOARD TO BE MODIFIED AS PER THE NOTES AND POWER SCHEMATIC.			A