

PWEXLEDP1

Stanilite Single Point Platinum Exit Lighting Bulkhead LED
Weather Proof Straight



Stanilite®

Component type	Emergency luminaire
Range	Single Point Platinum Exit Lighting
Model	N/A
Product status	Existing

The Stanilite single point Platinum exit lighting range features energy saving LED light source, efficient lithium power and fully retrofittable to previous generations of Quickfits.



ELECTRICAL

Operating mode	Maintained
Nominal voltage	240 V
Voltage type	AC
Max. system power	3.2 W
Nominal operation time	100000 h
Driver type	LED

CONSTRUCTION

With remote switch connection	No
With remote control	No
Mounting method	Ceiling surface mounting
With pictogram	Yes
With light source	Yes
Material housing	Plastic
Colour housing	White
Material cover	Plastic, opal
Degree of protection (IP)	IP65

PHOTOMETRIC

Lamp type	LED exchangeable
Photometric classification (C0)	D1.25
Photometric classification	C1.25

DIMENSIONS

Width	130.0 mm
Height/depth	190.0 mm
Length	380.0 mm

CERTIFICATES/APPROVALS

Compliant to AS/NZS CISPR 15	Yes
Compliant to AS/NZS 2293.3:2018	Yes
Compliant to AS/NZS 60598.1:2017	Yes
Compliant to AS/NZS 60598.2.22:2005	Yes

PWEXLEDP1

Stanilite Single Point Platinum Exit Lighting Bulkhead LED
Weather Proof Straight



Stanilite®

RELATED PRODUCTS

ACCESSORY



Item No: 0301301P
Required: No
Description: Stanilite Emergency Battery Pack
Lifepo4 3.2V 3.2Ah



Item No: 31PWE1
Required: No
Description: Stanilite Emergency Diffuser
Weather Proof 10W Picto Including Clear Lid