

1390

VIPER



SPECIFICATIONS:

3.9 kg	CRI 82+ 3k and 4k	CRI 70+ 5K	Class I	IP65	CE	5 Year warranty	Made in Australia
--------	----------------------	---------------	---------	------	----	--------------------	-------------------

CONSTRUCTION & DESIGN

- Surface Mount LED Weatherproof
- Housing constructed in die cast aluminium alloy and finished in durable powdercoat paint
- High impact and UV resistant polycarbonate prismatic diffuser with high output controlled light distribution
- Silicone gaskets and stainless steel fasteners provide IP65 weather protection
- 20mm cable entry at rear and three sides

OPTICAL & THERMAL PERFORMANCE

- LED thermal management incorporates both conduction and natural convection to transfer heat rapidly away from LED source
- Efficient optical control with no harsh cut off and ultra low glare
- Diffused very wide light distribution

ELECTRICAL SYSTEM

- Supplied standard with an integral non-dimmable driver and terminal block (refer to dimming option table)
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 52W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

CODE ORDERING GUIDE: PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1390-3K-52W-07 or 1390-3K-52W/DALI-07

SYSTEM POWER	COLOUR TEMP.	116° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		116°
52W	3K	1390-3K-52W	6365	4853
	4K	1390-4K-52W	6685	5144
	5K	1390-5K-52W	6501	5003


DIM CODE		52W
/DALI	Dali Dimming / Switch Dim	✓
/DSI	Digital Dimming	✓
/AD	Analogue Dimming 1-10V	x
/DIM	Leading & Trailing edge	x
	Non-dimmable	Std

COLOUR CODE	
-07	Textured Black



220

315



315