


2744
2745
2746

Aqua Kayl



2744 with clear glass

IP55



2745 with frosted glass



2746 with pattern frosted glass

CONSTRUCTION & DESIGN

- Recessed LED wall light
- Constructed in AISI 316 stainless steel in brushed finish with optional front trims of solid brass and solid copper
- Concealed LED for low glare illumination, perfect for illuminating stairs and walkways in up of down light position
- Optional blackout made from galvabond steel for recessing into concrete or masonry walls
- Built in constant current controller immune to voltage drop
- Ideal for illuminating stairs, walkways and feature lighting

TECHNICAL PERFORMANCE

- 3.9W total system power consumption with overload and short circuit protection
- > 65,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K, and 5K colour temperature with low colour shift over time

OPTICAL & THERMAL PERFORMANCE

- Reflector constructed in matte anodised high purity aluminium providing optimal performance and ultra low glare
- LED thermal management incorporates conduction to transfer heat rapidly away from LED source with optimal performance

ELECTRICAL SYSTEM

- **Input voltage 24V:** Connects to remote 24V DC power supply (TO BE ORDERED SEPARATELY)
- Parallel connection
- **Power supply instructions** Refer to pages 304 and 305

890

Blockout for recessing into concrete or masonry walls. Made from galvabond steel. To be ordered



	3K and 4K CRI >85	5K CRI >75	890 cut out 100x130				CE	IP55
--	----------------------	---------------	---------------------------	--	--	--	----	------

CODE ORDERING GUIDE: PRODUCT CODE /DIMMING SUFFIX (if required) – COLOUR SUFFIX
Example: 2744-3K-24V-28 or 2744-3K-24V/DALI-28

WATTAGE	COLOUR TEMPERATURE	PRODUCT CODES		INPUT VOLTAGE	HOT LED LUMENS
		> 55° WIDE			
3.9W	3K	2744-3K-24V	24V DC	370	
	4K	2744-4K-24V	24V DC	390	
	5K	2744-5K-24V	24V DC	425	
3.9W	3K	2745-3K-24V	24V DC	370	
	4K	2745-4K-24V	24V DC	390	
	5K	2745-5K-24V	24V DC	425	
3.9W	3K	2746-3K-24V	24V DC	370	
	4K	2746-4K-24V	24V DC	390	
	5K	2746-5K-24V	24V DC	425	

DIMMING OPTIONS: ADD SUFFIX AFTER THE CODE		3.9W	COLOUR OPTIONS: add suffix after the code	
/DALI	Dali Dimming	✓		-23 Solid Brass
	Switch Dim	✓		-28 Brushed Stainless Steel
/AD	Analogue Dimming 1-10V	✓		-35 Solid Copper
	Non Dimmable	STANDARD		

