

1002

KHO



## SPECIFICATIONS:

 0.3 kg	 82+ 3K and 4K	 70+ 5K	 67	 Tilt 30°	 SELV	IP44		 Available	 5 Year warranty	 Made in Australia
--	--	---	--	--	--	------	---	---	--	---

## CONSTRUCTION &amp; DESIGN

- Recessed LED adjustable downlight
- Trim and housing constructed in steel and finished in durable polyester powdercoat paint
- Recessed black housing with a deep recessed light source creating a dynamic visual impact with ultra low glare lighting performance

## OPTICAL &amp; THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with a deep recessed light source and ultra low glare

## ELECTRICAL SYSTEM


- Supplied standard with a remote leading and trailing edge mains dimmable driver, which is compatible with a range of dimming systems
- All drivers come with a quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz


## TECHNICAL PERFORMANCE

- 8W or 13W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Available in 3K, 4K or 5K colour temperature with very low colour shift over time

CODE ORDERING GUIDE: PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1002-3K-8W-01 or 1002-3K-8W/DALI-01

SYSTEM POWER	COLOUR TEMP.	 40° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		40°
8W	3K	1002-3K-8W	828	342
	4K	1002-4K-8W	870	360
	5K	1002-5K-8W	888	353
13W	3K	1002-3K-13W	1519	613
	4K	1002-4K-13W	1607	645
	5K	1002-5K-13W	1646	632



DIM CODE		8W	13W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓
	Leading & Trailing edge	Std	Std

COLOUR CODE	
-01	 Satin White

## OVERALL VIEW

