LEGEND LEGEND NOTE ELECTRICAL SERVICES SWITCHBOARD. Lx: LIGHT FITTING C/W NON-MAINTAINED EMERGENCY BATTERY PACK. ALL ELECTRICAL PENETRATIONS THROUGH THE ROOF TYPE AS NOTED. SHEETING ARE TO BE IN LINE WITH THE STRUCTURAL SWITCHBOARD / CONTROL PANEL NOT PROVIDED AS PART OF OR MECHANICAL SERVICES PENETRATIONS TO AVOID THE ELECTRICAL SUBCONTRACT. DEDICATED FLASHINGS FOR THE ELECTRICAL SERVICES. L1: 300 x 600 FLUSH RECESSED LED PANEL LIGHT. SINGLE POWER OUTLET. L2: 300 x 1200 FLUSH RECESSED LED PANEL LIGHT. DOUBLE POWER OUTLET. L3: 1200 SURFACE LED BATTEN C/W INTEGRAL SENSOR. SPECIAL PURPOSE POWER OUTLET. L4: EXISTING DOWNLIGHT TO BE RECOVERED FROM THE AREA OF DEMOLITION AND BE RELOCATED. SINGLE PHASE ISOLATOR. GL01 O GL01: DECORATIVE DALI DIMMABLE GARDEN STAKE LIGHT. THREE PHASE ISOLATOR. LMP01: DECORATIVE TRAILING EDGE DIMMABLE TABLE LAMP. ■ SIGNAGE CONNECTION. LMPO2: DECORATIVE TRAILING EDGE DIMMABLE TABLE LAMP. JUNCTION BOX. HLO1: DECORATIVE PENDANT HEAT LAMP. HAND DRYER CONNECTION. HL02 HL02: LINEAR UNDER SHELF HEAT LAMP. LIGHTING CONTROL SWITCH PANEL, TYPE AS NOTED. S1: REAR BAR DISPLAY DALI DIMMABLE LED STRIP LIGHT. ONE-WAY LIGHT SWITCH. S2: BAR COUNTER PELMET DALI DIMMABLE LED STRIP LIGHT. TWO-WAY LIGHT SWITCH. S3: REAR CAFE WALL DALI DIMMABLE LED STRIP LIGHT. CIRCUIT LINE. CEILING COFFER DALI DIMMABLE LED STRIP LIGHT. SWITCH LINE. S5: CEILING COFFER DALI DIMMABLE LED STRIP LIGHT. POWER CIRCUIT DESIGNATION. DB-x - Py DENOTES DB AND CIRCUIT. S6: WALL PELMET DALI DIMMABLE LED STRIP LIGHT. LIGHTING CONTROL CHANNEL REFERENCE. AMENITY WALL PELMET DALI DIMMABLE LED STRIP LIGHT. ELECTRICAL EQUIPMENT AS NOTED. S8: CAFE CEILING PELMET DALI DIMMABLE LED STRIP LIGHT. ▼ RJ45 COMMUNICATIONS OUTLET. S9: BAR DISPLAY SHELF SURROUND DALI DIMMABLE LED STRIP LIGHT. FIRE EVACUATION SPEAKER. WLO1: DECORATIVE TRAILING EDGE DIMMED WALL LIGHT. FIRE EMERGENCY WARNING CIE. WLO2: FOUR DECORATIVE FEATURE COLUMN TRAILING EDGE DIMMED WALL LIGHT. FIRE DETECTION CIE. WLO3: DECORATIVE AMENITY ENTRY TRAILING EDGE DIMMED WALL LIGHT. FIRE ALARM HORN. WLO4: DECORATIVE AMENITY MIRROR TRAILING EDGE DIMMED WALL LIGHT. THERMAL DETECTOR. PD01: DECORATIVE TRAILING EDGE DIMMED PENDANT LIGHT. THERMAL DETECTOR, TYPE B SEALED. DECORATIVE TRAILING EDGE DIMMED PENDANT LIGHT. PD02 🔿 ROOF MSSB-4 THERMAL DETECTOR WITHIN DUCT. DECORATIVE TRAILING EDGE DIMMED PENDANT LIGHT. PD03 🔿 DB-3 SMOKE DETECTOR. DECORATIVE TRAILING EDGE DIMMED PENDANT LIGHT. PD04 🔿 FUSE. PD05: DECORATIVE TRAILING EDGE DIMMED PENDANT LIGHT. PD05 🔿 REDLANDS SPORTS CLUB SINGLE PHASE. PD06 🔿 DECORATIVE TRAILING EDGE DIMMED PENDANT LIGHT. PD07 🔿 DECORATIVE TRAILING EDGE DIMMED PENDANT LIGHT. CIRCUIT BREAKER. DECORATIVE TRAILING EDGE DIMMED PENDANT LIGHT. PD08 **(**) PD09 🔿 PD09: DECORATIVE TRAILING EDGE DIMMED PENDANT LIGHT. LAWN BOWLS RESIDUAL CURRENT DEVICE. PD10 🔿 PD10: DECORATIVE TRAILING EDGE DIMMED PENDANT LIGHT. CONTACTOR - NORMALLY OPEN. PD11: GROUP OF THREE DECORATIVE TRAILING EDGE DIMMED PENDANT LIGHTS. CR-A CONTACTOR - NORMALLY CLOSED. RD01: RECESSED DALI DIMMABLE LED DOWNLIGHT. REFER TO DETAIL NOTED FOR THE AREA SHOWN HATCHED. ADDITIONAL OUTLETS & FITTINGS MAY BE SHOWN ON DETAIL. RD02: RECESSED DALI DIMMABLE LED DOWNLIGHT. LAWN BOWLS RDO3: RECESSED DALI DIMMABLE LED DOWNLIGHT. E1: GENERAL LED EMERGENCY LIGHT. EX: EMERGENCY LED EXIT LIGHT. SITE PLAN REFURBISHMENT WORKS SHADED SCALE 1: 750 E TENDER 17/06/2024 REV: DESCRIPTION: DATE: **ELECTRICAL DESIGN GROUP** THE COPYRIGHT OF THIS DRAWING **ELECTRICAL DESIGN GROUP BRISBANE** REDLANDS SPORTING CLUB **ELECTRICAL SERVICES** REMAINS THE PROPERTY OF THE PTY LTD ACN 092 710 793 ELECTRICAL DESIGN GROUP. CONSULTANTS ELECTRICAL BUILDING SERVICES LEGEND & SITE PLAN REFURBISHMENT TRADING AS: USE FIGURED DIMENSIONS GOLD COAST BRISBANE ELECTRICAL DESIGN GROUP IN PREFERENCE TO SCALE. P.O.Box 15, Sherwood Q.4075 ALL DIMENSIONS TO BE REVISION: Phone: (07) 3278 4375 VERIFIED ONSITE. E C3204a E01 Email: brisbane@edg.net.au ANSON ROAD, WELLINGTON POINT, QUEENSLAND 1:750 Web: www.edg.net.au