

1607-2L SNOVO



SPECIFICATIONS:

2.2 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	307x157	Rot 360°	Tilt 30°	SELV	IP40	CE	5 Year warranty	Made in Australia
--------	----------------------	---------------	---------	----------	----------	------	------	----	--------------------	-------------------

CONSTRUCTION & DESIGN

- Recessed LED adjustable downlight
- Trim and housing is constructed in die cast aluminium alloy and finished in durable polyester powder-coat paint
- Recessed and tilt adjustable housing with snoot gives directional flexibility for both ambient and feature lighting with low glare illumination
- Clear tempered glass

OPTICAL & THERMAL PERFORMANCE

- Heatsink manufactured from die-cast aluminium alloy for efficient heat dissipation
- Efficient optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with a remote leading and trailing edge mains dimmable driver (refer to dimming options table)
- All drivers come with quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60Hz

TECHNICAL PERFORMANCE



- 2x13W, 2x22W or 2x28W total system power consumption with overload and short circuit protection
- > 65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

CODE ORDERING GUIDE:

PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1607-2L-SP-3K-13W-01 or 1607-2L-SP-3K-13W/DALI-01

SYSTEM POWER	COLOUR TEMP.	PRODUCT CODE		HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT	
		20° SP	35° FL		SP	FL
2x13W	3K	1607-2L-SP-3K-13W	1607-2L-FL-3K-13W	3358	2168	2304
	4K	1607-2L-SP-4K-13W	1607-2L-FL-4K-13W	3552	2338	2476
	5K	1607-2L-SP-5K-13W	1607-2L-FL-5K-13W	3116	1766	1712
2x22W	3K	1607-2L-SP-3K-22W	1607-2L-FL-3K-22W	5332	3446	3636
	4K	1607-2L-SP-4K-22W	1607-2L-FL-4K-22W	5610	3678	3964
	5K	1607-2L-SP-5K-22W	1607-2L-FL-5K-22W	5012	2826	2740
2x28W	3K	1607-2L-SP-3K-28W	1607-2L-FL-3K-28W	7352	4778	5088
	4K	1607-2L-SP-4K-28W	1607-2L-FL-4K-28W	7626	4858	5192
	5K	1607-2L-SP-5K-28W	1607-2L-FL-5K-28W	6638	3816	3700



335

DIM CODE	OPTIONS	2x13W	2x22W	2x28W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓	✓
/DIM	Leading & Trailing edge	Std	Std	Std
	Non-dimmable	x	x	x

COLOUR CODE	DESCRIPTION
-01	Satin White (all-over)
-06	Matte Black (body and snoot)
	White body with black snoot

OTHER COMBINATION COLOUR

