

1410

CORBEL



SPECIFICATIONS:

0.4 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	105	Tilt 35°	SELV	IP54	CE	Available	5 Year warranty	Made in Australia
--------	----------------------	---------------	-----	----------	------	------	----	-----------	--------------------	-------------------

CONSTRUCTION & DESIGN

- Recessed LED adjustable downlight
- Constructed in die cast aluminium alloy and finished in durable polyester powder-coat paint
- Low profile adjustable LED downlight with high lumen output
- Clear tempered glass

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare
- Reflector is available in special matte lustre white treatment, allowing wider beam angle while maintaining excellent luminaire lumen output

ELECTRICAL SYSTEM



- Supplied standard with a remote leading and trailing edge mains dimmable driver (refer to dimming options table)
- All drivers come with a quick connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 13W or 22W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request


CODE ORDERING GUIDE: PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1410-3K-8W-01 or 1410-WR-3K-8W/DALI-01

SYSTEM POWER	COLOUR TEMP.	 41° STD REFLECTOR	 67° WHITE REFLECTOR	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT	
		PRODUCT CODE			41°	67°
13W	3K	1410-3K-13W	1410-WR-3K-13W	1679	1242	1228
	4K	1410-4K-13W	1410-WR-4K-13W	1776	1400	1378
	5K	1410-5K-13W	1410-WR-5K-13W	1558	1150	1116
22W	3K	1410-3K-22W	1410-WR-3K-22W	2666	1932	1920
	4K	1410-4K-22W	1410-WR-4K-22W	2805	2165	2152
	5K	1410-5K-22W	1410-WR-5K-22W	2506	1813	1802

DIM CODE	OPTIONS	13W	22W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓
/DIM	Leading & Trailing edge	Std	Std

COLOUR CODE	
-01	Satin White
-06	Matte Black



WHITE REFLECTOR OVERVIEW

