

1413

CORBEL

1418



SPECIFICATIONS:

0.8 kg	82+ 3K and 4K	70+ 5K	150	Tilt 35°	SELV	IP54	CE	Available	5 Year warranty	Made in Australia
--------	------------------	-----------	-----	----------	------	------	----	-----------	--------------------	-------------------

CONSTRUCTION & DESIGN

- Recessed LED adjustable downlight
- Constructed in die cast aluminium alloy and finished in durable polyester powdercoat paint
- Low profile adjustable LED downlight with high lumen output
- Clear tempered glass front

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with a remote driver (refer to dimming option table)
- All drivers come with a quick connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz


TECHNICAL PERFORMANCE

- 13W, 22W or 28W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

CODE ORDERING GUIDE: PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1413-3K-13W-01 or 1413-3K-13W/DALI-01

SYSTEM POWER	COLOUR TEMP.	53° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		53°
13W	3K	1413-3K-13W	1519	1164
	4K	1413-4K-13W	1607	1225
	5K	1413-5K-13W	1646	1195
22W	3K	1413-3K-22W	2414	1839
	4K	1413-4K-22W	2584	1936
	5K	1413-5K-22W	2618	1888
28W	3K	1418-3K-28W	3213	2483
	4K	1418-4K-28W	3380	2614
	5K	1418-5K-28W	3528	2560



OVERALL VIEW



DIM CODE		13W	22W	28W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓	✓
/DIM	Leading & Trailing edge	Std	Std	✓
	Non-dimmable	x	x	Std

COLOUR CODE	
-01	Satin White
-06	Matte Black