



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3269a - BROTHER'S LEAGUES CLUB, IPSWICH - BISTRO & KIDS ROOM

C3269a-0002(B).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION B - 26 JULY 2024

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L1	2700K LED	9 LAMP DECORATIVE PENDANT C/W REMOTE DALI DIMMABLE DRIVER SUPPLIED BY THE CLIENT ALLOW TO ASSEMBLE AND INSTALL. CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT.	SATIN BLACK CLEAR GLASS	CUSTOM FITTING	B
L2	2700K LED	3 LAMP DECORATIVE PENDANT C/W REMOTE DALI DIMMABLE DRIVER SUPPLIED BY THE CLIENT ALLOW TO ASSEMBLE AND INSTALL. CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT.	SATIN BLACK CLEAR GLASS	CUSTOM FITTING	B
L3	3 No 240VOLT 200LM +/- 10% 3000K E27 FILAMENT LEDs	DECORATIVE E27 PENDANT SWITCHED C/W 3 LAMP SUPPLIED BY THE CLIENT ALLOW TO ASSEMBLE AND INSTALL. CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT.	62 PIOMBO OUTSIDE 27 ORO FOGLIA INTERNAL	ENLIGHTENED LIVING TOSCOT NOTORIOUS 871 PENDANT	B
L4	2700K LED	DECORATIVE PENDANT C/W REMOTE DALI DIMMABLE DRIVER SUPPLIED BY THE CLIENT ALLOW TO ASSEMBLE AND INSTALL. CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT.	-	LUXBOX ILLI ACOUSTIC PENDANT HORIZONTAL LX-IL-L- OW-40-G	B
L5	2700K LED	DECORATIVE PENDANT C/W REMOTE DALI DIMMABLE DRIVER SUPPLIED BY THE CLIENT ALLOW TO ASSEMBLE AND INSTALL. CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT.	-	LUXBOX ILLI ACOUSTIC PENDANT PORTRAIT LX-IL-P- OW-40-G	B
L6	3 No 240VOLT 200LM +/- 10% 3000K E27 FILAMENT LEDs	DECORATIVE E27 PENDANT SWITCHED C/W 3 LAMP CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT. ALLOW TO ASSEMBLE	-	ENLIGHTENED LIVING WEPLIGHT PAULINA 116	A
L7	22W 3000K LED	SURFACE MOUNTED ADJUSTABLE SPOTLIGHT C/W REMOTE DALI DIMMABLE DRIVER	BLACK	GAMMA ILLUMINATION ARCHITEKT 1306SM- FL-3K-22W	B
L8	2 X 22W 3000K LED	TWIN HEAD RECESSED ADJUSTABLE DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION RETRA 1457-2L-FL-3K-22W	A
L9	240VOLT 200LM +/- 10% 3000K E14 FILAMENT LED	TABLE LAMP C/W A FLEX AND PLUG CONNECT3D TO A GPO CONCEALED WITHIN THE JOINERY.	BRASS	LIGHTERIOR KASA	A
L10	2 No 240VOLT 200LM +/- 10% 3000K E27 FILAMENT LEDs	WALL MOUNTED DECORATIVE LIGHT TO BE POSITIONED ON SITE AS DIRECTED BY THE ARCHITECT	BRASS	LIGHTERIOR TARA WALL LIGHT 2 LAMPA	A
L11	240VOLT 200LM +/- 10% 3000K E27 FILAMENT LED	TABLE LAMP C/W A FLEX AND PLUG CONNECT3D TO A GPO CONCEALED WITHIN THE JOINERY.	BLACK	LIGHTERIOR SFERIS TABLE LAMP MINI	A
L12	240VOLT 200LM +/- 10% 3000K E27 FILAMENT LED	TABLE LAMP C/W A FLEX AND PLUG CONNECT3D TO A GPO CONCEALED WITHIN THE JOINERY.	BLACK	LIGHTERIOR SFERIS TABLE LAMP SMALL	A
L13	240VOLT 200LM +/- 10% 3000K G9 LED	TABLE LAMP C/W A FLEX AND PLUG CONNECT3D TO A GPO CONCEALED WITHIN THE JOINERY.	RUST	JARDAN NELLY TABLE LAMP	A

**ELECTRICAL DESIGN GROUP**

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3269a - BROTHER'S LEAGUES CLUB, IPSWICH - BISTRO & KIDS ROOM					C3269a-0002(B).xls
ELECTRICAL EQUIPMENT SCHEDULE					
REVISION B - 26 JULY 2024					
THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L14		EXISTING COFFER LED STRIP LIGHTING TO BE RETAINED			A
L15		EXISTING TRUSS MOUNTED LED STRIP LIGHT TO BE RETAINED			A
L16	WARM WHITE LED	HORIZONTAL LED STRIP WITHIN AN ALUMINIUM EXTRUSION MOUNTED WITHIN THE CEILING BULKHEAD PELMET AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-12V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT	NATURAL	NEON PRODUCTS AUSTRALIA LF-DFB-WW-300-12 + PR-LIN172153-F	A
L17		EXISTING RECESSED DALI DIMMABLE DOWNLIGHT TO BE RETAINED RECIRCUITED AND CONTROLLED WHERE INDICATED			A
L18	28W 3000K LED	RECESSED 32 DEG BEAM DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	BLACK TRIM	GAMMA COBALT 1406-3K	A
L19	28W 3000K LED	RECESSED 32 DEG BEAM DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE TRIM	GAMMA COBALT 1406-3K	A
L20	12W/M 3000K LED	FLEXIBLE LED ROPE FLEX SCREW FIXED RECESSED INTO THE JOINERY PELMET AS PER THE ARCHITECTURAL DETAIL PROVIDE EACH L20 STRIP WITH A REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT LOCATED IN A CONCEALED ACCESSIBLE POSITION	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A
E1	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40.	WHITE	STANILITE SF1LEDP LITHIUM BATTERY	A
E2	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION MIN C0-D25 - C90-D25.	BLACK	STANILITE SF1LEDP LITHIUM BATTERY BLTRIM	A
EX	LED	EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-D3.2 - C90-E2.	WHITE LOGO GREEN BACKGROUND WHITE BODY	STANILITE PLQLEDP LITHIUM BATTERY	A
SINGLE POWER OUTLET		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A

**ELECTRICAL DESIGN GROUP**

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3269a - BROTHER'S LEAGUES CLUB, IPSWICH - BISTRO & KIDS ROOM					C3269a-0002(B).xls
ELECTRICAL EQUIPMENT SCHEDULE					
REVISION B - 26 JULY 2024					
THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
DOUBLE POWER OUTLET		DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
FLOOR MOUNTED OUTLET		SURFACE MOUNTED FLOOR BOX C/OUTLETS AS NOTED	STAINLESS STEEL FLOOR BOX WHITE OUTLETS	ELECTRIC CABLE DUCT SYSTEMS AFB20 - 4C-SKU040.000.0117	A
DB-1		EXISTING DISTRIBUTION BOARD (DB-1)			A
DB-2		EXISTING DISTRIBUTION BOARD (DB-2)			A
DB-3		EXISTING DISTRIBUTION BOARD (DB-3)			A
DB-4		EXISTING DISTRIBUTION BOARD (DB-4)			
MDB		EXISTING MDB TO BE UPGRADED TO ACCOMMODATE THE ADDITIONAL MCCB TO SUPPLY MSSB-2			A
MSSB-1		EXISTING MECHANICAL SERVICES SWITCHBOARD			
MSSB-2		NEW MECHANICAL SERVICES SWITCHBOARD BY THE MECHANICAL SUB CONTRACTOR			A
COMMUNICATIONS RACK (CR-A)		EXISTING COMMUNICATIONS RACK CR-A			A
COMMUNICATIONS OUTLET		RJ45 CAT-6 COMMUNICATIONS OUTLET, CABLED BACK TO CAT 6 PATCH PANELS IN RACK CR-A VIA 4-PAIR CAT-6 UTP CABLE. MOUNT UP TO 3 RJ45 OUTLETS PER MULTI-GANG FACEPLATE WITH SEPARATE PERMANENT LABELLING FOR EACH OUTLET. MOUNT AT 300 AFFL UNLESS NOTED OTHERWISE	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
FIRE INDICATOR PANEL (FIP)		EXISTING FIRE INDICATOR PANEL AND INTEGRAL ALARM AND EVACUATION PANEL TO AS1670. UPGRADE THE FIP AS REQUIRED TO ACCOMMODATE THE NEW WORKS			A
FIRE EVACUATION SPEAKER		RECESSED 5W 8-INCH CONE ALERT AND EVACUATION SPEAKER TO AS1670 C/W 100V MULTI-TAP TRANSFORMER AND FLUSH GRILLE WHITE UNLESS NOTE AS BLACK			A
SMOKE DETECTOR		SURFACE MOUNTED SMOKE DETECTOR TO AS1670. WHITE UNLESS NOTE AS BLACK			C