



LLEWELLYN MOTORS SPRINGFIELD - LOT 32 AUGUSTA PARKWAY, AUGUSTINE HEIGHTS																REV.01 02/03/2026
IMAGE	QTY	TYPE	NAME	DESCRIPTION	CODE	LED TYPE	WATTAGE	BEAM ANGLE	COLOUR TEMP.	CRI	IP RATING	FINISH	CONTROL GEAR	MOUNTING	OTHER DETAILS	LOCATION
		DL	DOWNLIGHT													
	22 ✓	DL1	LONDON	12W LED DIMMABLE COB DOWNLIGHT	R1081-WH-CW	CREE 1507 COB LED	12W	60°	4000K	>90	IP54	WHITE	DIMMABLE Remote Class II Driver DALI - Available upon request	RECESSED 90mm Cutout		TOILETS
	33 ✓	DL2	ATLANTA-150	25W LOW GLARE UGR<19 DEEP SET COB LED DOWNLIGHT	R1093-25-WH-SIL-TRI	Citizen COB	25W	60°	4000K	>90	IP54	WHITE	DIMMABLE Remote Class II Driver DALI - Available upon request	RECESSED 150mm Cutout		RECEPTION / BOARDROOM
	2 ✓	DL3	LENNOX-90	12W DEEP SET DIMMABLE LED DOWNLIGHT	R1076-WH-12W-CW-60	CREE COB LED	12W	60°	4000K	>90	IP54	WHITE	DIMMABLE Remote Class II Driver DALI - Available upon request	RECESSED 90mm Cutout		CUSTOMER LOUNGE
	32 ✓	DL5-A	CAPRI-195	LOW GLARE DIMMABLE COB LED DARKLIGHTER	R1355-40-WH-CW	Bridgelux COB	40W	60°	4000K	>90	IP44	WHITE	DIMMABLE Remote Class II Driver DALI - Available upon request	RECESSED 195mm Cutout		SHOWROOM
	12 ✓	DL5-B	CAPRI-195	LOW GLARE DIMMABLE COB LED DARKLIGHTER	R1355-40-WH-CW	Bridgelux COB	40W	36°	4000K	>90	IP44	WHITE	DIMMABLE Remote Class II Driver DALI - Available upon request	RECESSED 195mm Cutout		SHOWROOM
	23 ✓	DL6	CAPRI-140	LOW GLARE DIMMABLE COB LED DARKLIGHTER	R1353-18-WH-CW	Bridgelux COB	18W	60°	4000K	>90	IP44	WHITE	DIMMABLE Remote Class II Driver DALI - Available upon request	RECESSED 140mm Cutout		MEZZANINE CIRCULATION
PL PANEL																
	7 ✓	PL1	FRANKIE-25	LED UGR19 FLICKER FREE BACK LIT PANEL	R3205-UGR19-25-CW	2835 SMD LED	25W	90°	4000K	>80	IP40	WHITE	DIMMABLE Remote Class II Driver DALI - Available upon request	RECESSED 595mm x 595mm Cutout	RECESSED IN PLASTER (WHITE FINISH) + RECESS MOUNT FRAME R3212	KITCHEN / CLEANER
	32 ✓	PL2	FRANKIE-25	LED UGR19 FLICKER FREE BACK LIT PANEL	R3205-UGR19-25-CW	2835 SMD LED	25W	90°	4000K	>80	IP40	WHITE	DIMMABLE Remote Class II Driver DALI - Available upon request	RECESSED 595mm x 595mm T-BAR FRAME		OFFICES
BT BATTEN																
	22 ✓	BT1	HAWK-40	24w / 40w, 1200mm DUAL WATTAGE WEATHERPROOF BATTEN - IP65	R3540-TRI	Samsung SMD 2835 LED Chips	40W	110°	4000K	>80	IP65	WHITE	NON-DIMMABLE Class I Flicker Free LiIud Driver	SURFACE MOUNT		WORKSHOP / PARTS / TOOLS / REPAIR / COMPRESSOR
	5 ✓	BT1EM	HAWK-40	24w / 40w, 1200mm DUAL WATTAGE WEATHERPROOF EMERGENCY BATTEN - IP65	R3540-EM-TRI	Samsung SMD 2835 LED Chips	40W	110°	4000K	>80	IP65	WHITE	NON-DIMMABLE Class I Flicker Free LiIud Driver	SURFACE MOUNT		WORKSHOP / PARTS / TOOLS / REPAIR / COMPRESSOR
HB HI-BAY																
	20 ✓	HB1	ORBIT	200W POWER & CCT SELECTABLE LED HI BAY	R3118 + PC REFLECTOR	LED 2835	200W	120°	4000K	>80	IP65	BLACK	DIMMABLE Integral Class I Driver	SUSPENDED		WORKSHOP
LN LINEAR LIGHT																
	2	LN1	RAPIDLINE	RAPIDLINE LOW GLARE LINEAR LIGHTING SYSTEM - 2330mm	R2207-CW	Samsung SMD 2835 LEDs	45W	85°	4000K	>80	IP20	WHITE	DIMMABLE Flicker Free Driver DALI - Available upon request	SUSPENDED		RECEPTION
LS LED STRIP																
	13.3M	LS1	ONELINE	5w/m, 24VDC CONTINUOUS COB LED STRIP LIGHT	R2360-WW-V2	COB	5W/M	180°	3000K	>80	IP67		DIMMABLE DRIVER TBC	UNDER OVERHANGING CABINET	LENGHTS & DRIVERS & EXTRUSIONS TBC	LOUNGE / KITCHEN / MEETING ROOM / SHOWROOM
EM EMERGENCY																
	8	EM1	GHOST	LED WEATHERPROOF EMERGENCY BULKHEAD	R6260	SMD 2835	6W		5000K	>70	IP65	WHITE	BATTERY TYPE: LiFePO4 6.4V/1500mAh	SUSPENDED	Maintained / Non-Maintained	WORKSHOP
	3	EM2	R9999-AL	6W LED JUMBO BOX - STYLE EMERGENCY EXIT LIGHT	R9999-AL	SMD 2835	6W			>70	IP20	WHITE	BATTERY TYPE: Lithium Ion	SURFACE / SUSPENDED		WORKSHOP
	20	EM3	RAPIDFIRE	3w LED RAPIDFIRE EMERGENCY LIGHT ROUND LENS	R9991-WH		3W		6000K	>70	IP20	WHITE	BATTERY TYPE: LiFePO4 6.4V/1500mA	RECESSED 40-85mm Cutout		OFFICE AREAS
	6	EM4	RAPID BLADE	3w LED RAPID CONNECT EXIT LIGHT	R9996-R-WH	SMD 2835	3W			>70	IP20	WHITE	BATTERY TYPE: LiFePO4 6.4V/600mAh	RECESSED 410mm x 75mm Cutout		OFFICE AREAS

This printout is provided as a user service. Results, shown herein, are subject to practical tolerances associated with photometric measurement, site dimensional variations, aiming accuracy and control gear/lamp characteristics. Results, therefore, should only be used as a design guide/evaluation aid. Renderings are generated using diffuse (matt) surfaces, and standard reflectance's and colours (C70, W50, F20). These will influence the visual appearance of the illuminated surfaces. Therefore, any rendering shown can only be taken as an indication of how the area might visually appear. Reflection factors, if not standard values, are indicated. A maintenance factor of 0.8 has been applied to all luminaires. A maintenance policy should be adopted to support the maintenance factor of 0.8. This scheme has not been assessed for obtrusive light. Design compliance subject to accuracy of provided information and documentation.