

1255

1256

1257

## EVOKE SM



## SPECIFICATIONS:



7.2 kg



3K and 4K



5K



Class I



IP54



CE



Available



5 Year warranty



Made in Australia

## CONSTRUCTION &amp; DESIGN

- Surface mounted backlit LED luminaire
- Constructed in steel and finished in durable polyester powdercoat paint
- Sealed light engine and acrylic diffuser
- Also available in recessed and suspended versions

## OPTICAL &amp; THERMAL PERFORMANCE

- Unique optical design provides premium smooth light output
- Efficient optical control in with no harsh cut off and ultra low glare

## ELECTRICAL SYSTEM

- Supplied standard with an integral non-dimmable driver and terminal block (refer dimming options table)
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

## TECHNICAL PERFORMANCE

- 28W, 45W or 60W total system power consumption with overload and short circuit protection
- >116,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with very low colour shift over time

## CODE ORDERING GUIDE:

PRODUCT CODE


/

DIM CODE


-

COLOUR CODE

Example: 1255-3K-28W-01 or 1255-3K-28W/DALI-01

SYSTEM POWER	COLOUR TEMP.	 102° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		102°
28W	3K	1255-3K-28W	3612	3218
	4K	1255-4K-28W	3808	3392
	5K	1255-5K-28W	3739	3331
45W	3K	1256-3K-45W	5832	4957
	4K	1256-4K-45W	6138	5217
	5K	1256-5K-45W	6027	5123
60W	3K	1257-3K-60W	7516	6481
	4K	1257-4K-60W	7911	6821
	5K	1257-5K-60W	7767	6697

DIM CODE		28W	45W	60W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	x	x
/DIM	Leading & Trailing edge	✓	x	x
	Non-dimmable	Std	Std	Std

COLOUR CODE		
-01		Satin White

