




































LEGEND

	ELECTRICAL SERVICES SWITCHBOARD.
	SWITCHBOARD / CONTROL PANEL NOT PROVIDED AS PART OF THE ELECTRICAL SUBCONTRACT.
	SINGLE POWER OUTLET.
	DOUBLE POWER OUTLET.
	SPECIAL PURPOSE POWER OUTLET.
	SINGLE PHASE ISOLATOR.
	THREE PHASE ISOLATOR.
	SIGN CONNECTION.
	LIGHTING CONTROL SWITCH PANEL, TYPE AS NOTED.
	ONE-WAY LIGHT SWITCH.
	TWO-WAY LIGHT SWITCH.
	CIRCUIT LINE.
	SWITCH LINE.
	POWER CIRCUIT DESIGNATION. DENOTES DB AND CIRCUIT.
	LIGHTING CONTROL CHANNEL REFERENCE.
	ELECTRICAL EQUIPMENT AS NOTED.
	RJ45 COMMUNICATIONS OUTLET.
	RJ45 GAMING LINK OUTLET.
	GAMING FIBRE.
	FIRE INDICATOR PANEL.
	FIRE ALARM SYSTEM DOOR INTERFACE.
	FIRE ALARM SMOKE DETECTOR.
	FIRE ALARM THERMAL DETECTOR.
	RECESSED FIRE ALARM SPEAKER.
	FUSE.
	SINGLE PHASE.
	THREE PHASE.
	CURRENT TRANSFORMER C/W REMOVABLE LINK.
	FUSE LINK.
	COMBINED FUSE SWITCH.
	CIRCUIT BREAKER.
	ISOLATOR.
	RESIDUAL CURRENT DEVICE.
	CONTACTOR - NORMALLY OPEN.
	CONTACTOR - NORMALLY CLOSED.

LEGEND

	REFER TO DETAIL NOTED FOR THE AREA SHOWN HATCHED. ADDITIONAL OUTLETS & FITTINGS MAY BE SHOWN ON DETAIL.
	E1: GENERAL LED EMERGENCY LIGHT, RECESSED, WHITE.
	E2: GENERAL LED EMERGENCY LIGHT, MOUNTED IN A CUSTOM MDF BOX, WHITE.
	EX: WHITE EMERGENCY LED EXIT LIGHT, FRONT OF HOUSE.
	Lx: LIGHT FITTING C/W NON-MAINTAINED EMERGENCY BATTERY PACK. TYPE AS NOTED.
	L1: RECESSED 300 x 600 FLAT PANEL TROFFER, WHITE.
	L2: CEILING MOUNTED MOVING HEAD COLOUR WHEEL, BLACK.
	L3: 1200 LONG SURFACE IP65 BATTEN, LIGHT GREY.
	L4: EXISTING CARPARK POLE LIGHT TO BE MODIFIED.
	L5: NEW CARPARK POLE UTILISING A MODIFIED L4 FITTING.
	L6: NEW TWIN CARPARK POLE LIGHT TO MATCH EXISTING ADJACENT TWIN POLE LIGHT.
	RDL1: RECESSED DOWNLIGHT, WHITE.
	RDL2: RECESSED DOWNLIGHT, WHITE.
	RDL3: RECESSED DOWNLIGHT, WHITE.
	RDL4: RECESSED DOWNLIGHT, BLACK.
	RDL5: RECESSED DOWNLIGHT.
	SDL1: SURFACE MOUNTED CYLINDER SHADE C/W BUBBLE GLASS.
	SDL2: SURFACE MOUNTED CAN DOWNLIGHT, WHITE.
	SDL3: SURFACE MOUNTED SPOT LIGHT.
	SDL4: SURFACE MOUNTED 800DIA BALL LIGHT.
	SDL5: SURFACE MOUNTED SPOT LIGHT.
	SDL6: SURFACE MOUNTED ADJUSTABLE SPOT LIGHT, WHITE.
	SDL7: SURFACE MOUNTED CAN DOWNLIGHT, BLACK.
	WL1: WALL LIGHT, WHITE.
	WL2: WALL LIGHT, BRASS.
	WL3: WALL LIGHT, BRASS.
	PL1: DECORATIVE SUSPENDED PENDANT.
	CAT: CATENARY FESTOON LIGHTS WITH STAINLESS STEEL SUPPORT SYSTEM.
	UP1: GARDEN STAKE UPLIGHT FITTING, BLACK.
	H1: LINEAR HEAT LAMP.
	H2: LINEAR HEAT LAMP.
	H3: HANGING HEAT LAMP.
	HE/W: CEILING BULKHEAD MOUNTED LINEAR HEATER.
	CF1: 2180 DIA CEILING FAN, WHITE.
	TL1: TABLE LAMP.
	LP1: FITTING TYPE TO BE ADVISED.
	Sx: LED STRIP LIGHT, TYPE AS NOTED.

NOTE

ALL ELECTRICAL PENETRATIONS THROUGH THE ROOF SHEETING ARE TO BE IN LINE WITH THE STRUCTURAL OR MECHANICAL SERVICES PENETRATIONS TO AVOID DEDICATED FLASHINGS FOR THE ELECTRICAL SERVICES.

ELECTRICAL DESIGN GROUP BRISBANE
PTY LTD
ACN 092 710 793

THE COPYRIGHT OF THIS DRAWING
REMAINS THE PROPERTY OF THE
ELECTRICAL DESIGN GROUP.

TRADING AS:
ELECTRICAL DESIGN GROUP

USE FIGURED DIMENSIONS
IN PREFERENCE TO SCALE.

ALL DIMENSIONS TO BE
VERIFIED ONSITE.

ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

BRISBANE GOLD COAST

P.O.Box 15, Sherwood Q.4075
Phone: (07) 3278 4375
Email: brisbane@edg.net.au
Web: www.edg.net.au

PROJECT:
BRACKEN RIDGE TAVERN

154 BARRETT STREET, BRACKEN RIDGE

DRAWING:
ELECTRICAL SERVICES
LEGEND

SCALE:
NOT TO SCALE AT A1

PROJECT NO:
C3358a

DRAWING NO:
E01

REVISION:
C