

FLUSH SWITCHED SOCKETS WEATHERSHIELD®

Flush Mounted Switched Sockets

The surface range of switched sockets is also available in flush mounting. These models have a shallow mounting box for back wiring and a mechanism shroud for mounting directly onto mounting accessories such as brackets and wall boxes. Fixing screw caps and caps to cover mounting screws are provided. Screw caps must be in place to ensure maximum IP Rating. Overall dimensions fully assembled with shallow mounting box is 115 x 82 x 55mm, without mounting box 115 x 82 x 47mm.

Products are Authority approved and comply with AS 60529 'Degrees of Protection' and all relevant tests specified to AS/NZS 3112 Mines and Energy South Australia Approval S/1. Available in chemically resistant Grey, White, Cream and Terracotta.

Cat No.	Description	IP Rating
WSCF227/1	10A 250V ~ Surface Mounting Single Switched Socket	53
WSCF227/1/15	15A 250V ~ Surface Mounting Single Switched Socket	53
WSCF227/2	10A 250V ~ Surface Mounting Twin Switched Socket	53
WSCF227/2/15	15A 250V ~ Surface Mounting Twin Switched Socket	53
WSCF227/2X	10A 250V ~ Surface Mounting Twin Switched Socket with extra switch	53

For neon version use field fitted WNK (Weatherproof Neon Kit)
Terminals accommodate 3 x 2.5mm² cables.

Compact Single Switched Socket

Clipsal also offers the most compact weatherproof-switched outlet, small enough to mount onto 75mm² columns. The design includes a clear spring-loaded flap to ensure IP54 Rating when not in use. The surface mounted version has a mounting box with 3 x 25mm plain entries (plugs fitted) and a 25mm cut out in the base for back wiring. Overall dimensions 65 x 78 x 87mm. Overall dimensions flush 65 x 78 x 54mm. Terminals accommodate 4 x 2.5mm² cables. Fixing screw caps and caps to cover mounting screws are provided. Screw caps must be in place to ensure maximum IP Rating. Mines and Energy South Australia Approval S/1. Available in Grey, White or Brown.

Cat No.	Description	IP Rating
WSC228	10A 250V ~ Surface Mounted Single Switched Socket	54
WSCF228	10A 250V ~ Flush Mounted Single Switched Socket	54



WSCF227/2

Slim line profile

Surface Switched Sockets with IP54 Flap

For applications near the sea or areas where environment becomes aggressive, Clipsal offers an IP54 spring-loaded flap for use with the above socket outlet.

Cat No.	Description	IP Rating
WSCF227F/1	10A 250V ~ Surface Mounting Single Switched Socket with flap	54
WSCF227F/2	10A 250V ~ Surface Mounting Twin Switched Socket with flap	54

For neon version use field fitted WNK (Weatherproof Neon Kit)



WSC228