

1496

SCOOP MINI G2



SPECIFICATIONS:

| | | | | | | | | | | | |
|--------|----------------------|---------------|-----|----------|----------|------|------|----|-----------|-----------------|-------------------|
| 0.6 kg | CRI 82+ 3K and 4K | CRI 70+ 5K | 115 | Rot 350° | Tilt 80° | SELV | IP44 | CE | Available | 5 Year warranty | Made in Australia |
|--------|----------------------|---------------|-----|----------|----------|------|------|----|-----------|-----------------|-------------------|

CONSTRUCTION & DESIGN

- Recessed LED adjustable and rotatable wallwash downlight
- Constructed in pressure die cast aluminium alloy and finished in durable polyester powdercoat paint
- Adjustable LED downlight provides an off axis 80° tilt angle to ensure good utilisation and no light cut off
- Smooth positive retention and rotation mechanism
- Clear tempered glass front

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with a remote leading and trailing edge mains dimmable driver, which is compatible with a range of dimming systems
- All drivers come with quick connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction

TECHNICAL PERFORMANCE


- 8W or 13W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2

CODE ORDERING GUIDE:

PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1495-SP-3K-8W-01 or 1495-SP-3K-8W/DALI-01

| SYSTEM POWER | COLOUR TEMP. | PRODUCT CODE | | | | HOT LED LUMENS | LUMINAIRE LUMEN OUTPUT | |
|--------------|--------------|--------------|----------------|------------------|------|----------------|------------------------|------|
| | | | | | | | WFL | VWFL |
| 8W | 3K | | 1496-WFL-3K-8W | - | 828 | | 696 | - |
| | 4K | | 1496-WFL-4K-8W | - | 870 | | 756 | - |
| | 5K | | | - | 845 | | 718 | - |
| 13W | 3K | | - | 1496-VWFL-3K-13W | 1519 | | - | 1270 |
| | 4K | | - | 1496-VWFL-4K-13W | 1607 | | - | 1322 |
| | 5K | | - | | 1568 | | - | 1296 |



| DIM CODE | | 8W | 13W |
|----------|---------------------------|-----|-----|
| /DALI | Dali Dimming / Switch Dim | ✓ | ✓ |
| /DSI | Digital Dimming | ✓ | ✓ |
| /AD | Analogue Dimming 1-10V | ✓ | ✓ |
| | Leading & Trailing edge | Std | Std |

| COLOUR CODE | | |
|-------------|--|-------------|
| -01 | | Satin White |
| -06 | | |
| -10 | | |

OVERALL VIEW

