

## **ELECTRICAL DESIGN GROUP**

MAIN SWITCH:

SUPPLIED FROM:

**ELECTRICAL BUILDING SERVICES CONSULTANTS** P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375

250 NON AUTO LOAD

BREAK

DB-T

Website: www.edg.net.au Email: brisbane@edg.net.au

## C3585a - OXENFORD TAVERN **DISTRIBUTION BOARD DB-B REVISION A - 23 JULY 2025**

FAULT CURRENT:

CHASSIS SIZE:

6KA

96 POLE

C3585a-0005(A).xls

REV

Α

Α

		CHASSIS RATING:	250A		SUPPLY CABLE:	4C+E 50	Α			
		PHASES:	3				Α			
REFER TO THE EQUIPMENT SCHEDULE AND NOTES FOR ADDITIONAL REQUIREMENTS. PROVIDE THE DB WITH A FULL WIDTH EMPTY DIN RAIL TO ACCOMMODATE FUTURE CONTACTORS AND CONTROLS IN ADDITION TO THE CONTROLS INCLUDING THE DYNALITE EQUIPMENT PROVIDED AS PART OF THE INITIAL WORKS. PROVIDE THE DB WITH AN AS2293 EMERGENCY LIGHTING CONTROL SYSTEM TO CONTROL THE ASSOCIATED EMERGENCY LIGHTS. PROVIDE THE DB WITH SURGE PROTECTION. ENSURE THE SCHEDULE INCLUDES THE CIRCUIT USE AND LOCATION. ALLOW NEW SWITCHGEAR AND CONTROLS TO CONNECT ANY EXISTING DBS AND DB-3 CIRCUITS THAT REMAIN.										
CIRC	PH	CIRCUIT	CONTROL	CABLE	LOCATION	CIRCUIT	Α			
CINC	ГП	BREAKER (amps)	EQUIPMENT	SIZE ( mm <sup>2</sup> )	LOCATION	USE	Α			
D1	1	20	DCDO.	2.5	DISTRO	TV	Λ			

		T	· · · · · · · · · · · · · · · · · · ·	1 _ 1	ī		+
CIRC	PH	CIRCUIT BREAKER (amps)	CONTROL EQUIPMENT	CABLE SIZE ( mm <sup>2</sup> )	LOCATION	CIRCUIT USE	A
						Α	
						Α	
						Α	
							Α
							Α
							Α
							Α
							A
							A
1.4		00	DODO	0.5		LIQUITING	A
L1	1	20	RCBO	2.5		LIGHTING	A
L2	1	20	RCBO	2.5		LIGHTING	A
L3	1	20	RCBO	2.5		LIGHTING	A
L4	1	20	RCBO	2.5		LIGHTING	Α
L5	1	20	RCBO	2.5		LIGHTING	Α
L6	1	20	RCBO	2.5		FANS	Α
							Α
							A
							Α
							Α
							Α