





CLIFE-SM

Lifelight Emergency, Surface Mount, LP, Clevertest Plus



PRODUCT INFORMATION

Part Number	CLIFE-SM
MIC	AUD02310030001
Description	Lifelight Emergency, Surface Mount, LP, Clevertest Plus
Construction	Polycarbonate Enclosure
Mounting	Surface Mount
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.75kg
Operating Mode	Non-Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x High intensity LED
Operating Voltage	240V AC; 50Hz
Power Consumption	1.0 W (Standby), 4.2W (Max)
Inrush Current (Peak/Duration)	0.3A/3668µs
Earth Leakage	N/A
IP Rating	IP20
IK Rating	N/A
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D40, C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II double insulated

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	Battery
8050176	LED Head Assembly
8002934	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.