






LWELED

IP66/67 Weatherproof Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, All Pictograms, Single or Double Sided



PRODUCT INFORMATION	
Part Number	LWELED
MIC	AUA01320020002
Description	IP66/67 Weatherproof Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, All Pictograms, Single or Double Sided
Construction	Polycarbonate clear cover, glass reinforced nylon PA66 base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, Lifetime: >100,000hrs (AS/NZS2293.3 LSL=12Y/00M)
Operating Voltage	240V AC; 50Hz
Supply Current	TBC
Power Factor	TBC
Power Consumption	2.5 Watts (Standby), 3.7 Watts (Max)
Inrush Current (Peak/Duration)	17.1A / 138µs
Earth Leakage	TBC
IP Rating	IP66/IP67
Impact Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D6.3 C90=D5
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II Double Insulated  Noiseless (Clean) Earth (Ground) Terminal (Not a Protective Earth and used for EMC Purposes Only)



LWELED

IP66/67 Weatherproof Exit, Surface Mount, L10 Nanophosphate,
Clevertest Plus, All Pictograms, Single or Double Sided

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY
8002349	Emergency Driver
8002710	LED Panel

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order