

1069

Mini Aura



IP67

CONSTRUCTION & DESIGN

- Inground LED adjustable exterior uplighter
- Trim constructed in cast AISI 316 brushed stainless steel and body constructed in AISI 304 stainless steel and finished in black powdercoat paint
- High performance LED luminaire with low glare energy efficient illumination
- Screws and cable gland from AISI 304 stainless steel
- 8mm clear toughened cool touch glass and durable silicone seals providing IP67 protection
- Plastic installation well included with each fitting to facilitate installation and maintenance
- Ideal for large scale landscape projects and for illuminating commercial buildings and structures

TECHNICAL PERFORMANCE


- 8W or 13W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K and 5K colour temperature with low colour shift over time

OPTICAL & THERMAL PERFORMANCE


- Reflector and customised heatsink provides premium optical and thermal performance
- Efficient optical control various beam angles with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied completely assembled with integral leadin and trailing edge dimmable driver and three core orange cable
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz



installation well



200

243

154

SQUARE TRIM

Add Suffix /SQ after the code

3K and 4K
CRI >855K
CRI >75

IP67

TOTAL SYSTEM POWER CONSUMPTION = 8W / 13W

CODE ORDERING GUIDE: PRODUCT CODE /DIMMING SUFFIX (if required) – COLOUR SUFFIX

Example: 1069-SP-3K-8W-28 or 1069-SP-3K-8W/SQ/DALI-28

WATT	COLOUR TEMP.	 24° SP	 36° FL	 47-55° WFL-VWFL	HOT LED LUMENS
		PRODUCT CODES			
8W	3K	1069-SP-3K-8W	1069-FL-3K-8W	1069-WFL-3K-8W	828
	4K	1069-SP-4K-8W	1069-FL-4K-8W	1069-WFL-4K-8W	870
	5K	1069-SP-5K-8W	1069-FL-5K-8W	1069-WFL-5K-8W	888
13W	3K	1069-SP-3K-13W	1069-FL-3K-13W	1069-VWFL-3K-13W	1519
	4K	1069-SP-4K-13W	1069-FL-4K-13W	1069-VWFL-4K-13W	1607
	5K	1069-SP-5K-13W	1069-FL-5K-13W	1069-VWFL-5K-13W	1646

MODEL OPTIONS: ADD SUFFIX AFTER THE CODE
/SQ Square trim

DIMMING OPTIONS: ADD SUFFIX AFTER THE CODE

	8W	13W
/DALI Dali Dimming	✓	✓
/DSI Digital Dimming	✓	✓
Switch Dim	✓	✓
/AD Analogue Dimming 1-10V		✓

TRIM COLOUR OPTION: add suffix after the code

-28  Brushed Stainless Steel