

1413

CORBEL

1418



SPECIFICATIONS:

0.8 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	150	Rot 360°	Tilt 35°	SELV	IP54	CE	Available	5 Year warranty	Made in Australia
--------	----------------------	---------------	-----	----------	----------	------	------	----	-----------	-----------------	-------------------

CONSTRUCTION & DESIGN

- Recessed LED adjustable downlight
- Constructed in die cast aluminium alloy and finished in durable polyester powder-coat paint
- Low profile adjustable LED downlight with high lumen output
- Clear tempered glass front

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare
- Reflector is available in special matte lustre white treatment, allowing wider beam angle while maintaining excellent luminaire lumen output

ELECTRICAL SYSTEM

- Supplied standard with a remote driver (refer to dimming option table)
- All drivers come with a quick connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 13W, 22W or 28W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time


CODE ORDERING GUIDE: PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1413-3K-13W-01 or 1413-WR-3K-13W/DALI-01

SYSTEM POWER	COLOUR TEMP.	 21° SP	 41° STD REFLECTOR	 75° WHITE REFLECTOR	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT		
		PRODUCT CODE				21°	41°	75°
13W	3K	1413-SP-3K-13W	1413-3K-13W	1413-WR-3K-13W	1679	1375	1241	1235
	4K	1413-SP-4K-13W	1413-4K-13W	1413-WR-4K-13W	1776	1490	1427	1424
	5K	1413-SP-5K-13W	1413-5K-13W	1413-WR-5K-13W	1558	1247	1195	1192
22W	3K	1413-SP-3K-22W	1413-3K-22W	1413-WR-3K-22W	2666	2162	1965	1950
	4K	1413-SP-4K-22W	1413-4K-22W	1413-WR-4K-22W	2805	2336	2263	2236
	5K	1413-SP-5K-22W	1413-5K-22W	1413-WR-5K-22W	2506	1948	1888	1865
28W	3K	1418-SP-3K-28W	1418-3K-28W	1418-WR-3K-28W	3676	3045	2854	2852
	4K	1418-SP-4K-28W	1418-4K-28W	1418-WR-4K-28W	3813	3106	3105	3100
	5K	1418-SP-5K-28W	1418-5K-28W	1418-WR-5K-28W	3319	2731	2560	2555

DIM CODE	OPTIONS	13W	22W	28W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓	✓
/DIM	Leading & Trailing edge	Std	Std	✓
	Non-dimmable	x	x	Std

COLOUR CODE		
-01		Satin White
-06		Matte Black



WHITE REFLECTOR OVERVIEW

