

25-101

25-105

25-110

SERIES 25



SPECIFICATIONS: Weight - 1.1 kg per meter


5
Year warranty

Class I

IP20

CONSTRUCTION & DESIGN

- Series 25 three circuit track for surface mounting or suspended applications. Can be cut to length on site without any special tools
- Extruded aluminium profile available in satin white, black matte or bright silver powdercoat paint
- Three separately switchable circuits with common neutral
- Flat copper conductors 2.5mm². 16A max per circuit
- Pre punched holes for surface mounting 2 holes per metre
- All couplers and live ends can be re-configured on site to swap polarity or isolate sections as required, allowing limitless possible track layouts

CODE ORDERING GUIDE:

PRODUCT CODE			
Length (mm)	White	Black	Silver
1000	25-101	25-105	25-110
2000	25-201	25-205	25-210
3000	25-301	25-305	25-310

SUSPENSION COMPONENTS

25-906		Mounting clip and 1000mm rod (other rod length available on request)
GR2-1m GR2-2m GR2-3m GR2-4m GR2-5m		Stainless Steel Wire with Gripple Fastener and loop end on wire for looping around purlins, beams, roof trusses and other accessible roof features. Available in 1 to 5 metre lengths in 1m increments
25-075-50 25-075-100		Mounting Clip required for suspended applications 100mm clip can be used on a join together with 25-037

25-024	240V 16A	25-079	240V 16A
Live end for power feed		L coupler (can also be used for power feed)	
25-035	240V 16A	25-030	240V 16A
End cap with locking screw		T coupler (can also be used for power feed)	
25-037	240V 16A	25-031	240V 16A
Flush electrical coupler		X coupler (can also be used for power feed)	
25-078	240V 16A	25-033	240V 16A
Straight coupler (can also be used for power feed)		Flexible coupler (can also be used for power feed)	