

1305

SCOPE



SPECIFICATIONS:

1.1 kg	CRI 82+ 3K AND 4K	CRI 70+ 5K	Rot 355°	Tilt 90°	Class I	IP40	CE	5 Year warranty	Made in Australia
--------	----------------------	---------------	----------	----------	---------	------	----	--------------------	-------------------

CONSTRUCTION & DESIGN

- Track mounted LED adjustable spotlight
- Constructed in aluminium alloy and finished in durable polyester powder-coat paint
- Fully adjustable design with 355° rotation and 90° tilt
- Clear tempered glass providing IP40 protection
- Suitable with GAMMA SERIES 25, 3-Circuit Track System. Also compatible with many common European 3-Circuit Tracks

OPTICAL & THERMAL PERFORMANCE

- Reflector and integrated heatsink provides premium optical and thermal performance
- Efficient optical control in various beam angles with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with an integral leading and trailing edge mains dimmable driver (refer to dimming options table)
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 12W, 13W, 22W or 28W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ and Green Wall LED is available upon request

CODE ORDERING GUIDE:

PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1305-VNSP-3K-12W-01 or 1305-VNSP-3K-12W/DALI-01


SYSTEM POWER	COLOUR TEMP.	 14° VNSP	 24° SP	 36° FL	 55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT			
		PRODUCT CODE					VNSP	SP	FL	VWFL
12W	3K	1305-VNSP-3K-12W	-	-	-	1270	1092	-	-	-
	4K	1305-VNSP-4K-12W	-	-	-	1320	1134	-	-	-
	5K	1305-VNSP-5K-12W	-	-	-	1197	1028	-	-	-
13W	3K	-	1305-SP-3K-13W	1305-FL-3K-13W	1305-VWFL-3K-13W	1589	-	1362	1370	1337
	4K	-	1305-SP-4K-13W	1305-FL-4K-13W	1305-VWFL-4K-13W	1760	-	1524	1531	1451
	5K	-	1305-SP-5K-13W	1305-FL-5K-13W	1305-VWFL-5K-13W	1578	-	1365	1376	1300
22W	3K	-	1305-SP-3K-22W	1305-FL-3K-22W	1305-VWFL-3K-22W	2533	-	2121	2133	2065
	4K	-	1305-SP-4K-22W	1305-FL-4K-22W	1305-VWFL-4K-22W	2814	-	2379	2389	2252
	5K	-	1305-SP-5K-22W	1305-FL-5K-22W	1305-VWFL-5K-22W	2519	-	2123	2139	2023
28W	3K	-	1305-SP-3K-28W	1305-FL-3K-28W	1305-VWFL-3K-28W	3430	-	2816	2822	2808
	4K	-	1305-SP-4K-28W	1305-FL-4K-28W	1305-VWFL-4K-28W	3752	-	3079	3087	3042
	5K	-	1305-SP-5K-28W	1305-FL-5K-28W	1305-VWFL-5K-28W	3476	-	2820	2833	2770

DIM CODE	OPTIONS	12W	13W	22W	28W
/DALI	Dali Dimming	✓	✓	✓	✓
/DIM	Leading & Trailing edge	Std	Std	Std	Std

COLOUR CODE	
-03	Texture White
-07	Texture Black
-11	Texture Silver



077



151

162