

1115SM VIXO SM



SPECIFICATIONS:

1.5 kg	82+ 3K and 4K	70+ 5K	Rot 355°	Tilt 90°	Class I	IP54	CE	Available	Oval Beam Available	5 Year warranty	Made in Australia
--------	------------------	-----------	----------	----------	---------	------	----	-----------	---------------------	-----------------	-------------------

CONSTRUCTION & DESIGN

- Surface mounted LED adjustable spotlight
- Constructed in pressure die cast aluminium alloy and finished in durable polyester powdercoat paint
- Robust and versatile luminaire gives the flexibility for accent lighting or wide-area illumination
- Fully adjustable design with 355° rotation and 90° tilt
- Clear tempered glass, silicone seals and cable gland providing IP54 protection

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient thermal management provides premium optical and thermal performance
- Efficient optical control in various beam angles with no harsh cut off and ultra low glare
- Compatible with an Oval Beam Lens (Datasheet Available upon Request)

ELECTRICAL SYSTEM

- Supplied standard with an integral leading and trailing edge mains dimmable driver, compatible with a range of dimming systems
- Supplied with 100mm input cable
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 13W or 22W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

CODE ORDERING GUIDE:

PRODUCT CODE - COLOUR CODE

Example: 1115SM-SP-3K-13W-03 or 1115SM-SP-3K-13W/R/DALI-03

SYSTEM POWER	COLOUR TEMP.	 24° SP	 36° FL	 55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT		
		PRODUCT CODE				SP	FL	VWFL
13W	3K	1115SM-SP-3K-13W	1115SM-FL-3K-13W	1115SM-VWFL-3K-13W	1519	1214	1208	1198
	4K	1115SM-SP-4K-13W	1115SM-FL-4K-13W	1115SM-VWFL-4K-13W	1607	1275	1268	1261
	5K	1115SM-SP-5K-13W	1115SM-FL-5K-13W	1115SM-VWFL-5K-13W	1568	1244	1237	1231
22W	3K	1115SM-SP-3K-22W	1115SM-FL-3K-22W	1115SM-VWFL-3K-22W	2414	1945	1939	1898
	4K	1115SM-SP-4K-22W	1115SM-FL-4K-22W	1115SM-VWFL-4K-22W	2584	2043	2036	1998
	5K	1115SM-SP-5K-22W	1115SM-FL-5K-22W	1115SM-VWFL-5K-22W	2520	1993	1986	1949

DIM CODE		13W	22W
With circular surface mount base (Ø110x40mm)			
	Leading & Trailing edge	Std	Std
With rectangular surface mount base (170x95x40mm)			
/R/DALI	Dali Dimming / Switch Dim	✓	✓
/R/DSI	Digital Dimming	✓	✓
/R/AD	Analogue Dimming 1-10V	✓	✓
/R/DIM	Leading & Trailing edge	✓	✓

COLOUR CODE		
-03		Texture White
-07		Texture Black
-11		Texture Silver

