

SWINGBLADE EXIT



Versatile, Stylish, and Easy to Install

The Swingblade Exit is a sleek, blade-style emergency exit that combines premium design with easy installation and long-term reliability. Its innovative swinging blade adjusts after installation, making it ideal for sloped ceilings while ensuring optimal visibility and compliance.

This all-in-one solution includes a tamper-proof legend cover and directional decals for quick on-site configuration.

Powered by Lithium Iron Phosphate or Nanophosphate® batteries, its high-performance LED fittings offer superior reliability, energy efficiency, and low maintenance.

Applications



LP LITHIUM IRON
PHOSPHATE
PREMIUM
PREMIUM PROJECT PERFORMANCE

L10 LITHIUM
NANOPHOSPHATE®
OPTIMUM
NOTHING ELSE COMPETES WITH NANOPHOSPHATE®



Features and Benefits

- AS/NZS 2293.3 compliant
- Low 2.8W standby power consumption
- Wall or ceiling mounted
- All directional decals in one box
- Lithium Iron Phosphate or Nanophosphate® battery
- Clevertest Plus System compatible
- Theatre version available



SWINGBLADE EXIT

ORDERING INFORMATION		LP	L10
TEST OPTIONS / PART #	Standard	CSBLED	LSBLED
	Clevertest Plus System Compatible	Yes	Yes
	DALI	CSBLED-D2	LSBLED-D2
	Zoneworks® XT Hive	-	LSBLED-HVG
	Theatre Version	-	LSBLED-TH
Carton Quantity		6	
Weight - Single (Carton)		2.6kg (17kg)	
Dimensions (L x W x H)		435mm x 90mm x 263mm - Ceiling Mounted 435mm x 90mm x 230mm - Wall Mounted	
Directional Options		All Directional Inserts Included (Excluding Theatre Versions)	
Directional Options (Theatre Only)		Add Suffix to Part Number, -DS Double Sided, -R Pictograph, L (Left) or R (Right) ie. CSBLED-TH-DS-R	

POWER, LAMPS AND BATTERY		LP	L10
Power Consumption (Standby / Max)		3.8W / 5.6W	3.8W / 5.6W
Lamp(s)		24 x High Intensity LED, 100,000 Hour	
Battery		Lithium Iron Phosphate	Lithium Nanophosphate®
Voltage (V) / Capacity (mAh)		3.2V / 3200mAh	3.3V / 2500mAh
Charging Method		Intelligent Current Limited Constant Voltage	

TECHNICAL SPECIFICATIONS	
Operating Mode	Maintained
Voltage (V) Frequency (Hz)	220-240V(50Hz)
Construction - Body / Diffuser	Metal Frame, Acrylic & Polycarbonate Diffuser
Viewing Distance	24m
Mounting Type	Wall & Ceiling (Single & Double Sided)
Operating Temperature	1°C to 40°C
Ingress Protection Rating (IP)	IP20

ACCESSORIES	LP	L10
Cantilever Bracket (White)	CLVRBRT-SWINGBLADE	
Cantilever Bracket (Black)	CLVRBRT-SWINGBLADE-BLK	

CLASSIFICATION	LP	L10
C0	D6.3	D6.3
C90	E3.2	E3.2

SPACING TABLE AND MOUNTING HEIGHTS – AS/NZS 2293.1:2018 (MINIMUM LIGHT LEVEL OF 0.2 LUX)									
Classification	2.1m	2.4m	2.7m	3.0m	3.3m	3.6m	4.0m	4.5m	5.0m
D6.3	6.0	6.2	6.4	6.6	6.6	6.6	5.8	0.0	.0.0
E3.2	6.0	6.2	6.4	6.6	6.6	6.6	5.8	0.0	.0.0

For 1 lux and AS/NZS 2293.1:2005 spacing tables please visit: <https://clevertronics.com.au/spacing-tables/>

Based on minimum light level of 0.2 lux.
Maximum allowed mounting height is 2.7m but for exceptions see AS/NZS 2293.1.
Spacing classifications do not apply for theatre versions.

*Warranty information located at:
<https://clevertronics.com.au/warranty-statement/>



1



2

Dimensions (mm)

Product Configuration:

- 1 Ceiling Mounted
- 2 Wall Mounted

NOTE: If product is suspended below the Ceiling or Mounted on a metal surface the Swingblade bracket cover plate accessory (P/N:2740102) is required to cover the mains terminals.

clevertronics.co.nz
clevertronics.com.au

1 Caribbean Drive, Scoresby VIC 3179
P +61 3 9559 2700 F +61 3 9559 2799 E info@clevertronics.com.au

Clevertronics is committed to continuously improving its products.
All features and specifications are subject to change without prior notice.
_PRODUCT SHEETS – ANZ Swingblade 11JUN25

