

1136

MATRIX



OVERALL VIEW

SPECIFICATIONS:



2.2 kg



3K and 4K



5K



180



SELV



IP44



CE



Available



5 Year warranty



Made in Australia

CONSTRUCTION & DESIGN

- Recessed LED fixed downlight
- Trim is constructed in steel and finished in durable polyester powdercoat paint
- Housing constructed in die cast aluminium alloy and finished in durable polyester powdercoat paint
- The LED downlight has very high lumen output due to the brilliant optical control maintaining an ultra low glare performance
- Clear tempered glass

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with a remote driver (refer to dimming option table)
- All drivers come with a quick connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60Hz

TECHNICAL PERFORMANCE

- 95W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

CODE ORDERING GUIDE:


PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1136-SP-3K-95W-01 or 1136-SP-3K-95W/DALI-01

SYSTEM POWER	COLOUR TEMP.	 24° SP	 55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT	
		PRODUCT CODE			SP	VWFL
95W	3K	1136-SP-3K-95W	1136-VWFL-3K-95W	12015	10274	10111
	4K	1136-SP-4K-95W	1136-VWFL-4K-95W	12513	10788	10617
	5K	1136-SP-5K-95W	1136-VWFL-5K-95W	12976	10142	10150

DIM CODE		95W
/DALI	Dali Dimming / Switch Dim	✓
/DSI	Digital Dimming	✓
/AD	Analogue Dimming 1-10V	x
/DIM	Leading & Trailing edge	x
	Non-dimmable	Std

COLOUR CODE		
-01		Satin White
-06		Matte Black
-10		Bright Silver



205

190