

1004

MYLO



## SPECIFICATIONS:

|        |           |    |    |          |      |      |    |           |                     |                 |                   |
|--------|-----------|----|----|----------|------|------|----|-----------|---------------------|-----------------|-------------------|
| 0.3 kg | 3K and 4K | 5K | 95 | Tilt 30° | SELV | IP44 | CE | Available | Oval Beam Available | 5 Year warranty | Made in Australia |
|--------|-----------|----|----|----------|------|------|----|-----------|---------------------|-----------------|-------------------|

## CONSTRUCTION &amp; DESIGN

- Low profile recessed LED adjustable downlight
- Constructed in die cast aluminium alloy and finished in durable polyester powder-coat paint
- Low profile adjustable LED downlight with up to 22W system power and high lumen output
- Clear tempered glass

## OPTICAL &amp; THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Thermodynamically compact efficient heatsink design
- Efficient optical control with no harsh cut off and ultra low glare
- Compatible with an Oval Beam Lens
- Complies thermally with IC-4 and IC-F classification in accordance with AS/NZS 60598 (8W and 13W product only)

## ELECTRICAL SYSTEM

- Supplied standard with a remote leading and trailing edge mains dimmable driver (refer to dimming options table)
- All drivers come with quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz





## TECHNICAL PERFORMANCE

- 8W, 13W or 22W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

## CODE ORDERING GUIDE:


PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1004-SP-3K-8W-01 or 1004-SP-3K-8W/DALI-01

| SYSTEM POWER | COLOUR TEMP. |  24° SP |  36° FL |  47° WFL |  55° VWFL | HOT LED LUMENS | LUMINAIRE LUMEN OUTPUT |      |     |      |
|--------------|--------------|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|----------------|------------------------|------|-----|------|
|              |              | PRODUCT CODE                                                                               |                                                                                            |                                                                                             |                                                                                              |                | SP                     | FL   | WFL | VWFL |
| 8W           | 3K           | 1004-SP-3K-8W                                                                              | 1004-FL-3K-8W                                                                              | 1004-WFL-3K-8W                                                                              | -                                                                                            | 914            | 848                    | 857  | 850 | -    |
|              | 4K           | 1004-SP-4K-8W                                                                              | 1004-FL-4K-8W                                                                              | 1004-WFL-4K-8W                                                                              | -                                                                                            | 947            | 882                    | 888  | 880 | -    |
|              | 5K           | 1004-SP-5K-8W                                                                              | 1004-FL-5K-8W                                                                              | 1004-WFL-5K-8W                                                                              | -                                                                                            | 851            | 800                    | 805  | 797 | -    |
| 13W          | 3K           | 1004-SP-3K-13W                                                                             | 1004-FL-3K-13W                                                                             | -                                                                                           | 1004-VWFL-3K-13W                                                                             | 1589           | 1391                   | 1398 | -   | 1361 |
|              | 4K           | 1004-SP-4K-13W                                                                             | 1004-FL-4K-13W                                                                             | -                                                                                           | 1004-VWFL-4K-13W                                                                             | 1760           | 1557                   | 1562 | -   | 1477 |
|              | 5K           | 1004-SP-5K-13W                                                                             | 1004-FL-5K-13W                                                                             | -                                                                                           | 1004-VWFL-5K-13W                                                                             | 1578           | 1394                   | 1404 | -   | 1323 |
| 22W          | 3K           | 1004-SP-3K-22W                                                                             | 1004-FL-3K-22W                                                                             | -                                                                                           | 1004-VWFL-3K-22W                                                                             | 2533           | 2167                   | 2177 | -   | 2102 |
|              | 4K           | 1004-SP-4K-22W                                                                             | 1004-FL-4K-22W                                                                             | -                                                                                           | 1004-VWFL-4K-22W                                                                             | 2814           | 2430                   | 2438 | -   | 2292 |
|              | 5K           | 1004-SP-5K-22W                                                                             | 1004-FL-5K-22W                                                                             | -                                                                                           | 1004-VWFL-5K-22W                                                                             | 2519           | 2169                   | 2183 | -   | 2059 |

| DIM CODE | OPTIONS                   | 8W  | 13W | 22W |
|----------|---------------------------|-----|-----|-----|
| /DALI    | Dali Dimming / Switch Dim | ✓   | ✓   | ✓   |
| /DSI     | Digital Dimming           | ✓   | ✓   | ✓   |
| /AD      | Analogue Dimming 1-10V    | ✓   | ✓   | ✓   |
| /DIM     | Leading & Trailing edge   | Std | Std | Std |

| COLOUR CODE |  |             |
|-------------|--|-------------|
| -01         |  | Satin White |
| -06         |  | Matte Black |



## OVERALL VIEW

