

1826

## PEPPER MAX 2



## SPECIFICATIONS:

One way	0.9 kg	CRI 82+	Class I	IP54	CE	5 Year warranty
---------	--------	---------	---------	------	----	-----------------

## CONSTRUCTION &amp; DESIGN

- Surface mounted LED exterior wall light
- Constructed in pressure die cast aluminium alloy and finished in durable powder-coat paint
- Designed for both general illumination and for highlighting architectural features
- One way light distribution for direct or indirect illumination with low glare
- Clear tempered glass and silicone seals provides IP54 protection
- Can be mounted in any orientation

## OPTICAL &amp; THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare

## ELECTRICAL SYSTEM

- Supplied standard with an integral non dimmable driver and terminal block
- Input voltage 220-240V, 50/60 Hz

## TECHNICAL PERFORMANCE

- 12W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Available in selectable 3CCT - 3000K, 4000K or 5000K colour temperature with low colour shift over time

## CODE ORDERING GUIDE:

PRODUCT CODE - COLOUR CODE

Example: 1826-CCT-12W-07

SYSTEM POWER	COLOUR TEMP.	54° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		54°
12W	3000K	1826-CCT-12W	2080	1432
	4000K		2193	1507
	5000K		2306	1582

## COLOUR CODE

-07 Textured Black

