


C3743a - COOLUM BEACH HOTEL

C3743a-0002(E).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION E - 16 JUNE 2026

| THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm | | | | | |
|---|-------------------|---|--------------------|---|-----|
| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
| S1 | 14.4W/M 2700K LED | LED STRIP IN A RECTANGULAR CONFIGURATION (FOUR SIDES) WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER BEHIND THE TV AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | WHITE | RAPID LED R2334 2700K PLUS R2380 ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER | B |
| S2 | 14.4W/M 2700K LED | LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER WITHIN THE BAR FRONT FEATURE AS PER THE ELEVATION. MOUNT AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | NATURAL | RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER | A |
| S3 | 10W/M 2700K LED | IP67 LED FLEX SCREW FIXED RECESSED ONTO THE REAR BAR JOINERY AS PER THE ELEVATION. MOUNT AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT. | WHITE | RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER | A |
| S4 | 14.4W/M 2700K LED | LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER MOUNTED ON TOP OF THE SUSPENDED SHELF AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | NATURAL | RAPID LED R2334 PLUS ALUMINIUM EXTRUSION AND POWER SUPPLY & DALI CONTROLLER | A |
| S5 | 14.4W/M 2700K LED | THREE PARRALL RUNS OF LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER MOUNTED ON UNDERSIDE OF THE GAMING BAR BULKHEAD AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | WHITE EXTRUSION | RAPID LED R2334 PLUS ALUMINIUM EXTRUSION AND POWER SUPPLY & DALI CONTROLLER | B |
| S6 | 10W/M 2700K LED | IP67 LED FLEX SCREW FIXED RECESSED ONTO THE REAR BAR JOINERY AS PER THE ELEVATION. MOUNT AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT. | WHITE | RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER | A |



C3743a - COOLUM BEACH HOTEL


C3743a-0002(E).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION E - 16 JUNE 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
|------|---|--|--------------------|---|-----|
| S7 | 14.4W/M 2700K LED | LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER BEHIND THE MIRROR AS PER THE ELEVATION. MOUNT AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | NATURAL | RAPID LED R2334 PLUS ALUMINIUM EXTRUSION AND POWER SUPPLY & DALI CONTROLLER | A |
| S8 | 14.4W/M 2700K LED | LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RECESSED INTO THE CEILING AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | BLACK EXTRUSION | RAPID LED R2334 PLUS ALUMINIUM EXTRUSION AND POWER SUPPLY & DALI CONTROLLER | B |
| S9 | 14.4W/M 2700K LED | LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER MOUNTED WITHIN THE GAMING ROOM CURTAIN PELMET AS PER THE ELEVATION. MOUNT AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | WHITE | RAPID LED R2334 PLUS ALUMINIUM EXTRUSION AND POWER SUPPLY & DALI CONTROLLER | A |
| S10 | 14.4W/M 2700K LED | LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RISING VERTICALLY FROM THE FLOOR AND HORIZONALLY ACROSS THE DOORWAY IN THE GAMING ENTRY PORTAL Y AS PER THE ELEVATION. MOUNT AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | WHITE | RAPID LED R2334 PLUS ALUMINIUM EXTRUSION AND POWER SUPPLY & DALI CONTROLLER | B |
| PD01 | TRAILING EDGE DIMMABLE 240 VOLT 2700K E27 LED 1000 LUMENS +/- 10% | 720 DIA X 220 HIGH DECORATIVE PENDANT. CONFIRM THE SUSPENSION HEIGHT ONSITE WITH THE ARCHITECT | WHITE | FAT SHACK VINTAGE HAMLEN FABRIC PENDANT | B |
| PD02 | TRAILING EDGE DIMMABLE 240 VOLT 2700K E27 LED 750 LUMENS +/- 10% | 1000 DIA X 650 H DECORATIVE PENDANT. CONFIRM THE SUSPENSION HEIGHT ONSITE WITH THE ARCHITECT | RATTAN | THE STYLING REPUBLIC BETTY | B |
| PD03 | TRAILING EDGE DIMMABLE 240 VOLT 2700K E27 LED 750 LUMENS +/- 10% | 620 DIA X 380 HIGH DECORATIVE PENDANT. CONFIRM THE SUSPENSION HEIGHT ONSITE WITH THE ARCHITECT | NATURAL RATTAN | LIGHTHOUSE LANE PORTSEA PENDANT LIGHT | B |




C3743a - COOLUM BEACH HOTEL

C3743a-0002(E).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION E - 16 JUNE 2026

| THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm | | | | | |
|---|--|--|-----------------------------------|---|-----|
| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
| PD04 | TRAILING EDGE DIMMABLE 240 VOLT 2200K E27 G45 LED 250 LUMENS +/- 10% 15,000 HOUR LIFE LAMP | DECORATIVE PENDANT C/W 2000 BRAIDED TEXTILE CABLE. CONFIRM THE SUSPENSION HEIGHT ONSITE WITH THE ARCHITECT | LARGE CLEAR SHADE | FAT SHACK CHAPMAN GLASS NORD PENDANT P1189-CLR-LRG | D |
| PD05 | TRAILING EDGE DIMMABLE 240 VOLT 2200K E27 A60 LED 750 LUMENS +/- 10% 15,000 HOUR LIFE LAMP | 600 DIA X 600 HIGH DECORATIVE PENDANT. CONFIRM THE SUSPENSION HEIGHT ONSITE WITH THE ARCHITECT | GOLD FINISH CHAIN BRONZE FRAME | ABOUT SPACE ID 128010 TYPE A J23 26-00006380 | B |
| PD06 | TRAILING EDGE DIMMABLE 240 VOLT 2200K E27 A60 LED 750 LUMENS +/- 10% 15,000 HOUR LIFE LAMP | 1010 DIA X 580 HIGH DECORATIVE PENDANT. CONFIRM THE SUSPENSION HEIGHT ONSITE WITH THE ARCHITECT | GOLD FINISH CHAIN BRONZE FRAME | ABOUT SPACE ID 128010 TYPE B J23 26-00006380 | B |
| PD07 | TRAILING EDGE DIMMABLE 240 VOLT 2200K E27 G45 LED 250 LUMENS +/- 10% 15,000 HOUR LIFE LAMP | 250 DIA DECORATIVE PENDANT. CONFIRM THE SUSPENSION HEIGHT ONSITE WITH THE ARCHITECT | GOLD | FAT SHACK ORBITAL GLASS PENDANT SKU: P420- OPL-GLD | D |
| PD08 | TRAILING EDGE DIMMABLE 240 VOLT 2200K E14 LED 250 LUMENS +/- 10% 15,000 HOUR LIFE LAMP | 150 DIA X 140 HIGH DECORATIVE PENDANT. CONFIRM THE SUSPENSION HEIGHT ONSITE WITH THE ARCHITECT | BLACK | FAT SHACK STELLER REEDED GLASS P1138-AMB | D |
| PD09 | TRAILING EDGE DIMMABLE 240 VOLT 2200K E27 A60 LED 750 LUMENS +/- 10% 15,000 HOUR LIFE LAMP | 750 DIA X 250 H DECORATIVE PENDANT. CONFIRM THE SUSPENSION HEIGHT ONSITE WITH THE ARCHITECT | RATTAN | TEMPLE & WEBSTER ZAYN RATTAN PENDANT | B |
| PD10 | TRAILING EDGE DIMMABLE 240 VOLT 2700K E27 LED 750 LUMENS +/- 10% | 770 DIA X 490 HIGH DECORATIVE PENDANT. CONFIRM THE SUSPENSION HEIGHT ONSITE WITH THE ARCHITECT | ROPE | TEMPLE & WBSTER EVERETT IRON ROPE 3 LAMP PENDANT | B |
| PD11 | TRAILING EDGE DIMMABLE 240 VOLT 2700K B22 LED 750 LUMENS +/- 10% | 1020 DIA X 280 HIGH DECORATIVE PENDANT C/W BASIC SUSPENSION KIT. CONFIRM THE SUSPENSION HEIGHT ONSITE WITH THE ARCHITECT | RATTAN WHITE SUSPENSION | LIGHTING COLLECTIVE HANDWOVEN RATTAN PENDANT SHADE KIBUYU SKU: UF800PL | E |
| WL01 | INTEGRAL 8W 2700K LED | DECORATIVE 135 DIA X 80 DEEP WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAILS | AMBER | FAT SHACK SKU W1179-AMB-SAW | A |



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au


C3743a - COOLUM BEACH HOTEL

C3743a-0002(E).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION E - 16 JUNE 2026

| THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm | | | | | |
|---|--|---|--------------------------|---|-----|
| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
| WL02 | INTEGRAL 2 X 6W 3000K LED | DECORATIVE 2200 HIGH X 110 DEEP WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAILS | SAND | ABOUT SPACE MONOLITH | E |
| WL03 | INTEGRAL 2 X 6W 3000K LED | DECORATIVE 2200 HIGH X 110 DEEP WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAILS | SAND | ABOUT SPACE MONOLITH | E |
| WL04 | TRAILING EDGE DIMMABLE 240 VOLT 2200K G9 LED 250 LUMENS +/- 10% 15,000 HOUR LIFE LAMP | DECORATIVE 350 DIA X 150 PROJECTION WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAILS | ANTIQUE GOLD | ZEST LIGHTING MIKUMI PLEATED ANTIQUE GOLD BASE ROUND WALL LIGHT | B |
| WL05 | TRAILING EDGE DIMMABLE 240 VOLT 2200K B22 A60 LED 250 LUMENS +/- 10% 15,000 HOUR LIFE LAMP | DECORATIVE 350 DIA X 270MM H LARGE WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAILS | WHITE SHADE WHITE SCONCE | FAT SHACK VINTAGE W819-WHT-LRG-WHT CONE ADJUSTABLE SWIVEL ARM | B |
| WL06 | TRAILING EDGE DIMMABLE 240 VOLT 2200K E27 A60 LED 250 LUMENS +/- 10% 15,000 HOUR LIFE LAMP | DECORATIVE 320 DIA X 310 WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAILS | GRAPHITE | FATSHACK VINTAGE W119-GPH | B |
| WL07 | NO LONGER REQUIRED | | | | B |
| WL08 | NO LONGER REQUIRED | | | | B |
| WL09 | NO LONGER REQUIRED | | | | B |
| WL10 | TRAILING EDGE DIMMABLE 240 VOLT 2200K GU10 LED 250 LUMENS +/- 10% 15,000 HOUR LIFE LAMP | DECORATIVE 110 DEEP X 100 L X 90 HIGH WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAILS | BLACK | ABOUT SPACE SILFA | B |
| WL11 | INTEGRAL 15W 3000K LED | DECORATIVE 200 DIA X 70 DEEP WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAILS | WHITE | ABOUT SPACE KLIPS 200 DIA | B |
| WL12 | INTEGRAL 6W 3000K LED | DECORATIVE 30 DEEP X 110 HIGH WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAILS | BLACK | ABOUT SPACE JBO WALL LIGHT | B |




C3743a - COOLUM BEACH HOTEL

C3743a-0002(E).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION E - 16 JUNE 2026

| THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm | | | | | |
|---|--|--|--------------------|---|-----|
| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
| WLE | EXISTING WALL MOUNTED LIGHT FITTING TO BE RETAINED AND RESUPPLIED AS INDICATED. WITHIN ONE WEEK OF BEING AWARDED THE CONTRACT CONFIRM THE EXISTING LAMP TYPE AND CONTROL TYPE AS TRAILING EDGE, LEADING EDGE, DSI, 0-10, DALI OR SWITCHED. | | | | A |
| RD01 | 15W 3000K LED | 90 DIA RECESSED DOWNLIGHT C/W 24 DEG BEAM REMOTE DALI DIMMABLE DRIVER | WHITE | RAPID R1078-WH-15W-WW-DALI | A |
| RD02 | 15W 3000K LED | 75 DIA RECESSED ADJUSTABLE DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER | WHITE | RAPID R1077-WH-15W-WW-DALI | A |
| RD03 | 15W 3000K LED | RECESSED RECTANGLULAR DOUBLE HEAD ADJUSTABLE DOWNLIGHT C/W 24 DEG BEAM REMOTE DALI DIMMABLE DRIVER | WHITE | RAPID R1067-WH-15W-WW-DALI | A |
| RD04 | 18W 3000K LED | 150 DIA IP54 RECESSED DOWNLIGHT C/W 24 DEG BEAM REMOTE DALI DIMMABLE DRIVER | WHITE | RAPID R1093-18-WH-SIL-TRI DALI | B |
| RD10 | NO LONGER REQUIRED | | | | C |
| RD11 | 18W 3000K LED | 150 DIA IP54 RECESSED DOWNLIGHT C/W 24 DEG BEAM REMOTE DALI DIMMABLE DRIVER | WHITE | RAPID R1093-18-WH-SIL-TRI DALI | A |
| RDE | EXISTING LIGHT FITTING TO BE RETAINED AND RESUPPLIED AS INDICATED. WITHIN ONE WEEK OF BEING AWARDED THE CONTRACT CONFIRM THE EXISTING LAMP TYPE AND CONTROL TYPE AS TRAILING EDGE, LEADING EDGE, DSI, 0-10, DALI OR SWITCHED. | | | | A |
| SL01 | 15W 3000K LED | SURFACE MOUNTED 62 DIA 172 HIGH CAN DOWNLIGHT C/W 40DEG BEAM REMOTE DALI DIMMABLE DRIVER | WHITE | LUMEN 8 SOLIS SOROSU15930TR WHITE 15W 40DEG | B |
| SL02 | 40W 3000K LED | SURFACE MOUNTED 72 DIA 210 HIGH CAN DOWNLIGHT C/W 45DEG BEAM REMOTE DALI DIMMABLE DRIVER | WHITE | LUMEN 8 SOROSU40930ND WHITE 40W 40DEG | B |
| SL03 | 15W 3000K LED | SURFACE MOUNTED 62 DIA 172 HIGH CAN DOWNLIGHT C/W 40DEG BEAM REMOTE DALI DIMMABLE DRIVER | WHITE | LUMEN 8 SOLIS SOROSU15930TR WHITE 15W 40DEG | B |
| SL04 | 40W 3000K LED | SURFACE MOUNTED 72 DIA 210 HIGH CAN DOWNLIGHT C/W 45DEG BEAM REMOTE DALI DIMMABLE DRIVER AND A CUSTOM ANGLED TIMBER MOUNTING BLOCK TO ALLOW THE FITTING TO MOUNT VERTICALLY. THE MOUNTING BLOCK IS TO BE PAINTED TO MATCH THE FITTING COLOUR AND BE AS SMALL AS PRACTICAL. | WHITE | LUMEN 8 SOROSU40930ND WHITE 40W 40DEG | B |




C3743a - COOLUM BEACH HOTEL

C3743a-0002(E).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION E - 16 JUNE 2026

| THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm | | | | | |
|---|-----------------------|--|--|---|-----|
| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
| SLE | | EXISTING SURFACE MOUNTED LIGHT FITTING TO BE RETAINED AND RESUPPLIED AS INDICATED. WITHIN ONE WEEK OF BEING AWARDED THE CONTRACT CONFIRM THE EXISTING LAMP TYPE AND CONTROL TYPE AS TRAILING EDGE, LEADING EDGE, DSI, 0-10, DALI OR SWITCHED. | | | A |
| GL01 | 8W 3000K LED | GARDEN STAKE FITTING C/W REMOTE DALI DIMMABLE DRIVER MOUNT THE FITTING IN THE GARDEN AS PER THE ARCHITECTURAL DETAIL. IT IS ACCEPTABLE TO SUPPLY MULTIPLE UP2 FITTINGS ON THE SAME CHANNEL FROM A SINGLE SUITABLY SIZED DRIVER / POWER SUPPLY | BLACK | GAMMA ILLUMINATION RULLO 1373- FL-8W- 3K | A |
| BL01 | 2200K LED | TREE BUD LIGHTS. ALLOW A PC SUM FOR THE SUPPLY AND INSTALLATION OF EACH BL01 FITTING. | WHITE | ALLOW A PC SUM OF \$10,000.00 PLUS GST FOR THE SUPPLY OF EACH BD01 FITTING | A |
| G1 | 10W/M 2700K LED | IP67 LED FLEX SCREW FIXED IN THE GAMING CEILING FEATURE COFFER ABOVE THE PLANTER AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT. | WHITE | RAPID LED R2334 2700K PLUS R2380 ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER | B |
| R1 | 10W/M 2700K LED | IP67 LED FLEX SCREW FIXED IN THE GAMING CEILING FEATURE COFFER ABOVE THE PLANTER AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT. | WHITE | RAPID LED R2334 2700K PLUS R2380 ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER | B |
| FE | | EXISTING CEILING FAN AND ASSOCIATED CONTROLLER TO BE RETAINED. | | | A |
| F02 | | REPLACE THE EXISTING CEILING FAN AND CONTROLLER WITH A NEW 1320 DIA COASTAL GRADE FAN AND WALL MOUNTED CONTROLLER UTILISE THE EXISTING CIRCUIT | WHITE | VENTAIR SPIN1304WH | C |
| FS01 | 1W LED AT 500 CENTRES | REPLACE THE EXISTING FESTOON LIGHT WITH NEW 24V DC IP65 FESTOON LIGHTING TO BE FIXED TO A 316 STAINLESS STEEL WIRE SUPPORT SYSTEM. SUPPLY THE NEW FESTOON LIGHTS VIA REMOTE DALI DIMMABLE DRIVERS IN A CONCEALED ACCESSIBLE POSITIONS NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE LENGTH AND POSITION ON SITE CONNECT THE NEW FESTOON LIGHTS WITH A NEW SUPPLY TO THE NEW LIGHTING CONTROL SYSTEM | BLACK CABLE AND FIXINGS 316 STAINLESS STEEL SUPPORT AND FIXINGS | FIRE FLY FFC-LS-50-24VE27-BK | A |




C3743a - COOLUM BEACH HOTEL

C3743a-0002(E).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION E - 16 JUNE 2026

| THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm | | | | | |
|---|-------|--|----------------------------------|-----------------------------|-----|
| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
| FDE | | EXISTING FLOOD LIGHT TO BE RETAINED AND RESUPPLIED AS INDICATED. WITHIN ONE WEEK OF BEING AWARDED THE CONTRACT CONFIRM THE EXISTING LAMP TYPE AND CONTROL TYPE AS TRAILING EDGE, LEADING EDGE, DSI, 0-10, DALI OR SWITCHED. | | | A |
| E1 | LED | EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40. | WHITE | CLEVERTRONICS LLIFE | A |
| E2 | | EXISTING EMERGENCY LIGHT TO BE RETAINED | | | A |
| EX E3 | | EXISTING EMERGENCY EXIT LIGHT TO BE RETAINED | | | A |
| EX | LED | EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING SURFACE MOUNT OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-D1.25- C90-D2 | WHITE | CLEVERTRONICS LUBPRO-SM | A |
| EX BK | LED | EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING SURFACE MOUNT OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-D1.25- C90-D2 | BLACK | CLEVERTRONICS LUBPRO-SM-BLK | A |
| CHANNEL x | | CONTROL CHANNEL WITH A NUMERICAL REFERENCE. REFER TO THE POWER AND LIGHTING CONTROL SCHEMATIC / SCHEDULE | | | A |
| LIGHTING CONTROL SWITCH PANEL 1 (SP1) | | EXISTING DYNALITE ANTUMBRA DISPLAY TO BE CONNECTED TO THE NEW LIGHTING CONTROL SYSTEM. REMOVE THE EXISTING MANUAL LIGHTING CONTROLS THAT BECOME REDUNDANT. | | | A |
| LIGHTING CONTROL SWITCH PANEL 2 (SP2) | | 6-BUTTON PROGRAMMABLE SWITCH PANEL C/W CENTRAL LCD DISPLAY MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE. REMOVE THE EXISTING MANUAL LIGHTING CONTROLS THAT BECOME REDUNDANT. | ALUMINIUM | DYNALITE ANTUMBRA DISPLAY | A |
| LIGHTING CONTROL SWITCH PANEL 3 (SP3) | | 6-BUTTON PROGRAMMABLE SWITCH PANEL C/W CENTRAL LCD DISPLAY MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE. REMOVE THE EXISTING MANUAL LIGHTING CONTROLS THAT BECOME REDUNDANT. | ALUMINIUM | DYNALITE ANTUMBRA DISPLAY | A |
| SINGLE POWER OUTLET | | SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O. | WHITE UNLESS NOTED AS BLACK (BK) | CLIPSAL C2000 SERIES | E |



C3743a - COOLUM BEACH HOTEL

C3743a-0002(E).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION E - 16 JUNE 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
|------------------------------------|-------|--|----------------------------------|----------------------|-----|
| AUTO DOOR SINGLE POWER OUTLET (AD) | | SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION LOCATED CONCEALED WITHIN THE AUTO DOOR HEAD MULLION RATING 10A U.N.O. | WHITE | CLIPSAL C2000 SERIES | A |
| DOUBLE POWER OUTLET | | DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O. | WHITE UNLESS NOTED AS BLACK (BK) | CLIPSAL C2000 SERIES | A |
| SIGN CONNECTION | | COORDINATE THE LOCATION AND CONNECTION WITH THE SIGN CONTRACTOR ENSURING THE CONNECTION ARE PROVIDED WITH APPROPRIATE WEATHER PROTECTION AND ARE CONCEALED FROM VIEW. | | | A |
| DB-1 | | EXISTING DISTRIBUTION BOARD DB-1 LOCATED ON THE MEZZANINE LEVEL TO BE PROVIDED WITH NEW SWITCHGEAR TO ACCOMMODATE THE NEW CIRCUITS AS NOTED IN THE DISTRIBUTION BOARD DB-1 SCHEDULE. ANY EXISTING CIRCUITS THAT BECOME REDUNDANT DUE TO THE WORKS ARE TO BE REMOVED. PROVIDE DB-1 WITH A WALL MOUNTED DIN RAIL CUBICAL TO ACCOMMODATE THE NEW DB-1 LIGHTING CONTROL GEAR. ENSURE THE CUBICAL CONTAINS AT LEAST ONE SPARE 600 WIDE HORIZONTAL DIN RAIL IN ADDITION TO THAT NECESSARY TO ACCOMMODATE THE INITIAL DYNALITE CONTROL EQUIPMENT. | | | A |
| DB-2 | | EXISTING DISTRIBUTION BOARD DB-2 LOCATED ON THE MEZZANINE LEVEL TO BE USED AS THE GAMING DB BY THE GAMING ELECTRICIAN. ANY EXISTING CIRCUITS THAT BECOME REDUNDANT DUE TO THE WORKS ARE TO BE REMOVED. RELOCATE ANY EXISTING CIRCUITS THAT REMAIN TO DB-1. | | | A |
| DB-3 | | EXISTING DISTRIBUTION BOARD DB-3 TO BE PROVIDED WITH NEW SWITCHGEAR TO ACCOMMODATE THE NEW CIRCUITS AS NOTED IN THE DISTRIBUTION BOARD DB-3 SCHEDULE. ANY EXISTING CIRCUITS THAT BECOME REDUNDANT DUE TO THE WORKS ARE TO BE REMOVED. PROVIDE DB-3 WITH A WALL MOUNTED DIN RAIL CUBICAL TO ACCOMMODATE THE NEW DB-3 LIGHTING CONTROL GEAR. ENSURE THE CUBICAL CONTAINS AT LEAST ONE SPARE 600 WIDE HORIZONTAL DIN RAIL IN ADDITION TO THAT NECESSARY TO ACCOMMODATE THE INITIAL DYNALITE CONTROL EQUIPMENT. | | | A |
| DB-4 | | EXISTING DISTRIBUTION BOARD DB-4 TO BE PROVIDED WITH NEW SWITCHGEAR TO ACCOMMODATE THE NEW CIRCUITS AS NOTED IN THE DISTRIBUTION BOARD DB-4 SCHEDULE. ANY EXISTING CIRCUITS THAT BECOME REDUNDANT DUE TO THE WORKS ARE TO BE REMOVED. PROVIDE DB-4 WITH A WALL MOUNTED DIN RAIL CUBICAL TO ACCOMMODATE THE NEW DB-4 LIGHTING CONTROL GEAR. ENSURE THE CUBICAL CONTAINS AT LEAST ONE SPARE 600 WIDE HORIZONTAL DIN RAIL IN ADDITION TO THAT NECESSARY TO ACCOMMODATE THE INITIAL DYNALITE CONTROL EQUIPMENT. | | | A |
| MSB | | EXISTING HOTEL MAIN SWITCHBOARD LOCATED ON THE MEZZANINE LEVEL TO REMAIN. | | | A |