

**C3785a - AVEO ROBINA GARDENS RETIREMENT LIVING****C3785a-0002(B).xls****ELECTRICAL EQUIPMENT SCHEDULE****REVISION B - 11 SEPTEMBER 2026**

THE EQUIPMENT SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/links.html					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L1	12W 3000K LED	90 DIA IP54 RECESSED DOWNLIGHT C/W 24 DEG BEAM REMOTE DRIVER	WHITE	RAPID R1078-WH-12W-WW-60	A
L2	5W 3000K LED	ADJUSTABLE 12V DC GARDEN SPIKE LIGHT MOUNTED WITHIN THE ENTRY BULKHEAD GARDEN PROVIDE A COMMON REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	BLACK	RAPID R6017-WW	A
L3	15W 3000K LED	90 DIA IP54 RECESSED DOWNLIGHT C/W 24 DEG BEAM REMOTE DALI DIMMABLE DRIVER	BLACK	RAPID R1078-WH-15W-WW-60 DALI	A
L4	16W 4000K LED	300 X 600 LED FLAT PANEL C/W REMOTE DRIVER AND PLASTERBOARD RECESS KIT	WHITE	RAPID R3207-TRI-RM	A
L5	25W 3000K LED	RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DRIVER	WHITE	RAPID R1093-25-WH-SIL-TRI	B
L6	15W 3000K LED	90 DIA IP54 RECESSED DOWNLIGHT C/W 24 DEG BEAM REMOTE DRIVER	WHITE	RAPID R1078-WH-15W-WW-60	A
L7	18W 3000K LED	150 DIA IP54 RECESSED DOWNLIGHT C/W 24 DEG BEAM REMOTE DRIVER	WHITE	RAPID R1093-18	A
L8	13W 3000K LED	P54 RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DRIVER	WHITE	RAPID R1352-13-WH-WW	A
S1	14.4W/M 3000K LED	THREE RUNS OF RECESSED LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER WITHIN THE JOINERY AS PER THE ELEVATION AND THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH A REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 3000 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY	A
S2	14.4W/M 3000K LED	TWO RUNS OF RECESSED LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER WITHIN THE JOINERY AS PER THE ELEVATION AND THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH A REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 3000 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY	A
S3	10W/M 3000K LED	IP67 LED FLEX SCREW FIXED WITHIN THE BAR COUNTER FRONT KICK AS PER THE SECTION AND ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT.	WHITE	RAPID LED R2321 OR R2322 - 3000K + POWER SUPPLY	A

C3785a-0002(B).xls

Pages inc. any attach. 1 of 7

**C3785a - AVEO ROBINA GARDENS RETIREMENT LIVING****C3785a-0002(B).xls****ELECTRICAL EQUIPMENT SCHEDULE****REVISION B - 11 SEPTEMBER 2026**

THE EQUIPMENT SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/links.html					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
S4	14.4W/M 3000K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RECESSED INTO THE OVERHEAD JOINERY AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH A REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CIRCUIT AND SWITCH THE S4 WITH THE EXISTING ADJACENT ROOM LIGHTING.	NATURAL	RAPID LED R2334 3000 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY	B
S5	14.4W/M 3000K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RECESSED INTO THE OVERHEAD JOINERY AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH A REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 3000 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY	A
S6	10W/M 3000K LED	IP67 LED FLEX SCREW FIXED WITHIN THE ENTRY WALL AS PER THE ELEVATION AND ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT.	WHITE	RAPID LED R2321 OR R2322 - 3000K + POWER SUPPLY	A
S7	10W/M 3000K LED	IP67 LED FLEX SCREW FIXED WITHIN THE ENTRY BULKHEAD PER THE PLAN / ELEVATION AND ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT.	WHITE	RAPID LED R2321 OR R2322 - 3000K + POWER SUPPLY	A
S8	2250 LUMENS / M 4000K LED	EXTRUSION C/W OPAL DIFFUSER AND INTEGRAL DRIVER TO BE FIXED TO THE ENTRY SIDE OF THE EXISTING HORIZONTAL CORD SUCH THAT THE UNDERSIDE OF THE FITTING IS LEVEL WITH THE UNDER SIDE OF THE CORD. THE FITTING IS TO SPAN FROM ONE WALL TO THE WALL ON THE OPPOSITE SIDE.	WHITE	KLIK SYSTEMS KALLI 060 BEAM DI	A
S9	14.4W/M 3000K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RECESSED INTO THE CINEMA CEILING AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH A REMOTE DALI DIMMABLE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 3000 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY DALI	A
S10	14.4W/M 3000K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RECESSED INTO THE CINEMA CEILING AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH A REMOTE DALI DIMMABLE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 3000 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY DALI	A

**C3785a - AVEO ROBINA GARDENS RETIREMENT LIVING****C3785a-0002(B).xls****ELECTRICAL EQUIPMENT SCHEDULE****REVISION B - 11 SEPTEMBER 2026**

THE EQUIPMENT SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/links.html					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
S11	6-15W 4000K LED PER FITTING	REPLACE THE EXISTING WALL LIGHT IN THE CEILING COFFER WITH A 3000 LENGTH OF SURFACE TRACK WITH FOUR ADJUSTABLE FITTINGS SELECT THE WATTAGE ON SITE AS DIRECTED BY THE ARCHITECT	WHITE	RAPID LED 6 WIRE SURFACE TRACK AND R2580-WH-TRI-36 FITTINGS	A
S12	14.4W/M 4000K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER IN SECTIONS AS NECESSARY TO AVOID THE STRUCTURE MOUNTED ON TOP OF THE LOWER CORD TO ILLUMINATE UPWARDS. PROVIDE THE STRIP WITH A REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 4000 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY	A
S13	4500 LUMENS / M 4000K LED	11500 LONG EXTRUSION C/W OPAL DIFFUSER AND INTEGRAL DALI DIMMABLE DRIVER TO BE FIXED TO THE UNDERSIDE OF THE LOWER CORD OF THE TRUSS TO ILLUMINATE DOWNWARDS.	WHITE	KLIK SYSTEMS KALLI 060 BEAM DI	A
S14	4500 LUMENS / M 4000K LED	3500 LONG EXTRUSION C/W OPAL DIFFUSER AND INTEGRAL DALI DIMMABLE DRIVER TO BE FIXED TO THE UNDERSIDE OF THE LOWER CORD OF THE TRUSS TO ILLUMINATE DOWNWARDS.	WHITE	KLIK SYSTEMS KALLI 060 BEAM DI	A
S15	14.4W/M 3000K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RECESSED INTO THE LOWER HAND RAIL SUPPORT AS PER THE ARCHITECTURAL DETAIL TO ILLUMINATE UPWARDS. PROVIDE THE STRIP WITH A REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 3000 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY	A
S16	10W/M 3000K LED	IP67 LED FLEX SCREW FIXED WITHIN THE BAR COUNTER TOP FRONT AS PER THE SECTION AND ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT.	WHITE	RAPID LED R2321 OR R2322 - 3000K + POWER SUPPLY	A
S17	10W/M 3000K LED	IP67 LED FLEX SCREW FIXED WITHIN THE BAR COUNTER BULKHEAD AS PER THE SECTION AND ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT.	WHITE	RAPID LED R2321 OR R2322 - 3000K + POWER SUPPLY	A
S18	14.4W/M 3000K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER MOUNTED UNDER THE LOW LEVEL JOINERY AS PER THE ARCHITECTURAL DETAIL TO ILLUMINATE ONTO THE FLOOR. PROVIDE THE STRIP WITH A REMOTE DALI DIMMABLE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 3000 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY	B



C3785a - AVEO ROBINA GARDENS RETIREMENT LIVING

C3785a-0002(B).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION B - 11 SEPTEMBER 2026

THE EQUIPMENT SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/links.html					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
S19	14.4W/M 3000K LED	THREE HORIZONTAL RUN OF LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RECESSED INTO THE UNDERSIDE OF THE OVERHEAD JOINERY TO ILLUMINATE DOWN THE SPLASH BACK AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH A REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 3000 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY	B
S20	14.4W/M 3000K LED	TWO RUNS OF RECESSED LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER WITHIN THE REAR BAR JOINERY SHELF TO ILLUMINATE UPWARDS AS PER THE ELEVATION AND THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH A REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 3000 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY	B
S21	10W/M 3000K LED	IP67 LED FLEX SCREW FIXED WITHIN THE RECEPTION COUNTER FACE AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT.	WHITE	RAPID LED R2321 OR R2322 - 3000K + POWER SUPPLY	B
PL1	TBA	ENTRY DECORATIVE PENDANT LIGHT. CONFIRM THE SUSPENSION HEIGHT WITH THE ARCHITECT ALLOW TO ASSEMBLE AND INSTALL.	TBA	ALLOW A PC SUM OF \$10,000.00 PLUS GST FOR THE SUPPLY OF THE PLO1 FITTING	B
PL2	3000k LED	REPLACE THE EXISTING POOL TABLE PENDANT WITH A NEW DECORATIVE 2200 LONG PENDANT LIGHT. CONFIRM THE SUSPENSION HEIGHT WITH THE ARCHITECT	BLACK CEILING PLATE AND FITTING	ABOUT SPACE ASP FOURTY5 CUSTOM ROUND 3000K 2200 LONG	A
PL3	EXISTING PENDANT LIGHT ALONG WITH ALL ASSOCIATED CONTROLS AND CABLING TO BE REMOVED				A
WL1	3W 240 VOLT 3000K G9 LED	REPLACE THE EXISTING WALL LIGHT WITH TWO DECORATIVE WALL LIGHTS ONE UP ONE DOWN AS PER THE ARCHITECTURAL DETAIL. CONFIRM THE MOUNTING HEIGHT WITH THE ARCHITECT	GOLD BRASS MATT OPAL SHADE	2 X FAT SHACK VINTAGE BROOKLYN WALL LAMP	A
WL2	8W 3000K INTEGRAL LED	600 WIDE DECORATIVE WALL LIGHT. CONFIRM THE MOUNTING HEIGHT WITH THE ARCHITECT	GOLD BRASS	FAT SHACK VINTAGE BOLTON VANITY MEDIUM SKU W1085-GLD-MED	A
WL3	3W 3000K INTEGRAL LED	DECORATIVE WALL LIGHT. CONFIRM THE MOUNTING HEIGHT WITH THE ARCHITECT	BRASS BASE OPAL ROUND GLASS	ABOUT SPACE CATERPILLAR WALL A 120DIA	A



C3785a - AVEO ROBINA GARDENS RETIREMENT LIVING

C3785a-0002(B).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION B - 11 SEPTEMBER 2026

THE EQUIPMENT SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/links.html					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
WL4	12W 3000K INTEGRAL LED	REPLACE THE EXISTING WALL LIGHT WITH A NEW WALL LIGHT.	WHITE	FAT SHACK VINTAGE STONEBROOK CONCRETE EXTERIOR SKU W522 WHT	A
WL5	EXISTING WALL LIGHT ALONG WITH ALL ASSOCIATED CONTROLS AND CABLING TO BE REMOVED				A
WL6	EXISTING HIGH LEVEL SPOT LIGHT ALONG WITH ALL ASSOCIATED CONTROLS AND CABLING TO BE REMOVED				A
WL7	COORDINATE THE POWER SUPPLY LOCATION AND CONNECTION WITH THE MIRROR INSTALLER ENSURING THE CONNECTION IS PROVIDED WITH APPROPRIATE WEATHER PROTECTION AND ARE CONCEALED FROM VIEW.				A
E1	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40.	WHITE	CLEVERTRONICS CLIFE	A
E2	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40.	BLACK	CLEVERTRONICS CLIFE BLK	A
F1	EXISTING CEILING FAN AND ALL ASSOCIATED CONTROLS AND CABLING TO BE REMOVED				A
F2	EXISTING CEILING FAN AND ALL ASSOCIATED CONTROLS AND CABLING TO BE REMOVED PROVIDE A NEW 3700 DIA CEILING FAN AND WALL MOUNTED CONTROLLER		WHITE WITH SILVER TRIM	BIG ASS ESSENCE HVLS FAN	A
F3	PROVIDE A NEW 3700 DIA CEILING FAN AND WALL MOUNTED CONTROLLER		WHITE WITH SILVER TRIM	BIG ASS ESSENCE HVLS FAN	A
F4	EXISTING CEILING FAN AND ALL ASSOCIATED CONTROLS AND CABLING TO BE REMOVED PROVIDE A NEW 1500 DIA CEILING FAN AND WALL MOUNTED CONTROLLER		WHITE	BIG ASS HAIKU + DOWN ROD	A
F5	PROVIDE A NEW 1500 DIA CEILING FAN AND WALL MOUNTED CONTROLLER		WHITE	BIG ASS HAIKU + DOWN ROD	A
F6	PROVIDE A NEW 1500 DIA CEILING FAN C/W INTEGRAL LIGHT AND WALL MOUNTED CONTROLLER		WHITE	BIG ASS HAIKU COASTAL MARINE-GRADE + DOWN ROD	A
F7	EXISTING WALL FAN AND ALL ASSOCIATED CONTROLS AND CABLING TO BE REMOVED				A
SWITCH PANEL SP1		MULTI GANG LIGHTING SWITCH PANEL C/W SWITCHES, DIMMERS AND FAN CONTROLLERS AS PER THE LIGHTING SCHEMATIC. MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	STAINLESS STEEL	CLIPSAL B SERIES FACEPLATE	B
SWITCH PANEL SP2		MULTI GANG LIGHTING SWITCH PANEL C/W SWITCHES, DIMMERS AND FAN CONTROLLERS AS PER THE LIGHTING SCHEMATIC. MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL B SERIES FACEPLATE	B

**C3785a - AVEO ROBINA GARDENS RETIREMENT LIVING****C3785a-0002(B).xls****ELECTRICAL EQUIPMENT SCHEDULE****REVISION B - 11 SEPTEMBER 2026**

THE EQUIPMENT SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/links.html					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
DALI POT DIMMER / SWITCH		ONE-WAY DALI LIGHT SWITCH / DIMMER C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	SMARTSCAPE DALI RD20 CLIPSAL C2000	A
DALI		ONE-WAY DALI LIGHT SWITCH / DIMMER MOUNTED ON SP1 / SP2 AS PER THE LIGHTING CONTROL SCHEMATIC	WHITE	SMARTSCAPE DALI RD20 CLIPSAL C2000	A
ONE-WAY LIGHT SWITCH		ONE-WAY LIGHT SWITCH C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL C2000 SERIES 30USM	A
TWO-WAY LIGHT SWITCH		TWO-WAY LIGHT SWITCH C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL C2000 SERIES 30USM	A
FAN CONTROLLER 1 (FC1)		FAN CONTROLLER CONNECTED TO THE FAN AS DETAILED ON THE LIGHTING CONTROL SCHEMATIC VIA A CAT 5 CABLE. THE FAN CONTROLLER IS TO BE MOUNTED AS PART OF SP1 / SP2	WHITE	BIGG ASS ESSENCE WIRED DALI CONTROLLER	B
FAN CONTROLLER 2 (FC2)		BLUE TOOTH FAN CONTROLLER CONNECTED TO THE FAN CIRCUIT AS PER THE LIGHTING CONTROL SCHEMATIC TO CONTROL THE CHANNEL 14, 15 AND 16. THE FAN CONTROLLER IS TO BE MOUNTED AS PART OF SP2.	WHITE	BIGG ASS SKU: C-BTWC-03-04-00-US	B
FAN CONTROLLER 3 (FC3)		BLUE TOOTH FAN CONTROLLER CONNECTED TO THE FAN CIRCUIT AS PER THE LIGHTING CONTROL SCHEMATIC TO CONTROL THE CHANNEL 18 AND 19 FANS. THE FAN CONTROLLER IS TO BE MOUNTED AS PART OF SP2.	WHITE	BIGG ASS SKU: C-BTWC-03-04-00-US	B
FAN CONTROLLER 4 (FC4)		BLUE TOOTH FAN CONTROLLER CONNECTED TO THE FAN CIRCUIT MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	BIGG ASS SKU: C-BTWC-03-04-00-US	B
FAN CONTROLLER 5 (FC5)		BLUE TOOTH FAN CONTROLLER CONNECTED TO THE FAN CIRCUIT AS PER THE LIGHTING CONTROL SCHEMATIC TO CONTROL THE CHANNEL 8 AND 9 FANS. THE FAN CONTROLLER IS TO BE MOUNTED AS PART OF SP1.	WHITE	BIGG ASS SKU: C-BTWC-03-04-00-US	B
EXIST		EXISTING ELECTRICAL OUTLET / FITTING TO REMAIN AS IS, UNLESS NOTED OTHERWISE.			A
SINGLE POWER OUTLET		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT ABOVE BENCH U.N.O.	WHITE	CLIPSAL C2000 SERIES	A
DOUBLE POWER OUTLET		DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT ABOVE BENCH U.N.O	WHITE	CLIPSAL C2000 SERIES	A
DOUBLE POWER OUTLET (USB)		DOUBLE POWER OUTLET C/W USB CHARGER AND CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE	CLIPSAL 2000 SERIES + 30USBCM MECH	A

**C3785a - AVEO ROBINA GARDENS RETIREMENT LIVING****C3785a-0002(B).xls****ELECTRICAL EQUIPMENT SCHEDULE****REVISION B - 11 SEPTEMBER 2026**

THE EQUIPMENT SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/links.html					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
SINGLE-PHASE ISOLATOR		SINGLE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT32	A
THREE-PHASE ISOLATOR		THREE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT35	B
COMMUNICATIONS RACK CR-A		UPGRADE THE EXISTING COMMUNICATIONS RACK TO ACCOMMODATE THE NEW COMMUNICATIONS OUTLETS. UPDATE THE LABELLING.			A
COMMUNICATIONS OUTLET		RJ45 CAT-6 COMMUNICATIONS OUTLET, CABLED BACK TO A PATCH PANEL IN CR-A VIA 4-PAIR CAT-6 UTP CABLE. MOUNT UP TO 3 RJ45 OUTLETS PER MULTI-GANG FACEPLATE WITH SEPARATE PERMANENT LABELLING FOR EACH OUTLET. MOUNT ABOVE BENCH UNLESS NOTED OTHERWISE	WHITE	CLIPSAL C2000 SERIES	A
COMMUNICATIONS RACK CR-A		UPGRADE THE EXISTING COMMUNICATIONS RACK TO ACCOMMODATE THE NEW COMMUNICATIONS OUTLETS. UPDATE THE LABELLING.			A
DB-A		EXISTING DISTRIBUTION BOARD TO REMAIN. PROVIDE DB-A WITH A 63A THREE PHASE MCB TO SUPPLY THE NEW DB-B VIA A NEW CONCEALED 4C+E 35mm SUBMAIN. RELOCATE THE EXISTING LIGHTING CIRCUITS FROM DB-A TO DB-B.			A
DB-B		NEW DISTRIBUTION BOARD DB-B REFER TO THE NOTES AND DISTRIBUTION BOARD DB-B SCHEDULE FOR ADDITIONAL INFORMATION AND REQUIREMENTS. PROVIDE DB-B WITH A 4C+E 25mm SUBMAIN FROM A NEW 63A MCB IN DB-A. PROVIDE A SHOP DRAWING OF THE DB FOR APPROVAL INCLUDING ALL LIGHTING CONTROLS AS PART OF THE SHOP DRAWING.			A
FIRE SPEAKER		AS1670.1 RECESSED FIRE ALARM SPEAKER C/W WHITE GRILLE, UNLESS NOTED AS BLACK (BK)			A
MANUAL CALL POINT		EXISTING MANUAL CALL POINT TO BE RELOCATED AS INDICATED			A
FIRE INDICATOR PANEL (FIP)		EXISTING FIRE INDICATOR PANEL TO BE UPGRADED AS NECESSARY TO ACCOMMODATE THE NEW RECESSED SPEAKERS. REPLACE THE ZONE PLAN WITH A NEW FRAMED ZONE PLAN REFLECTING THE NEW LAYOUT.			A