


PHANTOM G2

884501 | 884502 | 884503 | 884504

Gamma Illumination

LED PANEL LIGHT RANGE



FEATURES

- Flicker-free driver with 1.2m SAA Flex & Plug.
- White powder coated aluminium narrow frame.
- 50,000 hours lifetime L70 at 25°C.
- Edge lit LED with brightness uniformity.
- For applications in grid or t-bar ceilings only.
- Recommended for use in office spaces, schools, open business task areas, reading & writing.

FINISH



PRODUCT SPECIFICATIONS

Product Code	884501-3k 884501-4k	884502-4k	884503-4k	884504-4k
Dimensions	1195x295x10	595x595x10	595x295x10	1195x595x10
LED	40W	40W	20W	70W
LED Lumens	4000Lm	4000Lm	1800Lm	7000Lm
LED Life	50,000 Hours	50,000 Hours	50,000 Hours	50,000 Hours
Power Factor	>0.95	>0.95	>0.95	>0.95
Input Voltage	220-230V AC 50Hz	220-230V AC 50Hz	220-230V AC 50Hz	220-230V AC 50Hz

•Also available - 28watt & Dali - 2950 lumens -

ACCESSORIES

Frame for recessing into plaster ceilings.

Product Code	PF-3012	PF-6060	PF-3060	PF-6012
Compatible Product	884501	884502	884503	884504
Dimensions	1200x300	600x600	600x300	1200x600

Screwless frame for installation where surface mounting is required.

Product Code	887001	887002	887003	887004
Compatible Product	884501	884502	884503	884504
Dimensions	1200x300x43	600x600x43	600x300x43	1200x600x43

Frame with screws for installation where surface mounting is required.

Product Code	887005	887006	887007	887008
Compatible Product	884501	884502	884503	884504
Dimensions	1200x300x43	600x600x43	600x300x43	1200x600x43

