

1243

FREESTYLE 350



SPECIFICATIONS:

Upward throw	2.5 kg	CRI 82+ 3K and 4K	Class I	IP20	CE	5 Year warranty	Made in Australia
--------------	--------	----------------------	---------	------	----	--------------------	-------------------

CONSTRUCTION & DESIGN

- Wall mounted LED uplight luminaire for indoor use
- Constructed in steel and finished in durable polyester powder-coat paint
- Forward throw optics and diffused acrylic cover for a smooth even light distribution and low glare performance
- Modular gear tray assembly for quick installation

OPTICAL & THERMAL PERFORMANCE

- Forward throw optics and efficient heatsink provides premium optical and thermal performance
- Concealed light source and indirect illumination provides soft ambient lighting

ELECTRICAL SYSTEM

- Supplied standard with an integral leading and trailing edge mains dimmable driver and terminal block (refer to dimming options table)
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 28W total system power consumption with overload and short circuit protection
- > 65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K or 4K colour temperature with very low colour shift over time
- CRI 90+ is available upon request

CODE ORDERING GUIDE:

PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1243-3K-28W-03 or 1243-3K-28W/DALI-03

SYSTEM POWER	COLOUR TEMP.	85x60° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		85x60°
28W	3K	1243-3K-28W	3612	1578
	4K	1243-4K-28W	3808	1661

DIM CODE	OPTIONS	28W
/DALI	Dali Dimming / Switch Dim	✓
/DSI	Digital Dimming	✓
/AD	Analogue Dimming 1-10V	✓
/DIM	Leading & Trailing edge	Std
	Non-dimmable	x

COLOUR CODE		
-03		Textured White
-07		Textured Black
-11		Textured Silver

270



350



80